

Modular Flat Telephone Cable

pro-POWER



Description

Stranded PACW, 4 core, PVC insulation, PVC sheath

Application

Telephone handset cord or line cord

Construction

Conductor

Material : Plain Annealed Copper Wire (PACW)
Wire Gauge : 26 AWG
Conductor Area CSA : 0.14mm²
Stranding : 7/0.16mm

Insulation

Material : PVC
Nominal Inner Diameter : 0.95 mm
Colours : A : Black, B : Red, C : Green and D : Yellow

Sheath

Material : PVC
Nominal Outer Diameter : 2.5mm × 5mm
Colour : Black


Physical Properties

Minimum Bend Radius : 25mm
Operating Temperature : -15°C to +70°C

Electrical Properties

Nominal DC Resistance : 134Ω / km
Voltage Test : Core to core : 1,000V AC / 1 minute

Diagram



Part Number Table

Description	Part Number
Cable, FCC68, 4 Core, Black, 100m	TEM0039-2009

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER