

RTD Foamcut



706-3696

## TECHNICAL DATA

# RTD Foamcut

## Metal Cutting Lubricant Spray

### Description

ROCOL RTD Foamcut is a metal cutting lubricant specially formulated to provide extreme pressure cutting performance in an economical to use foaming aerosol.

ROCOL RTD Foamcut is suitable for all metal cutting operations on a wide range of ferrous and non ferrous metals, including copper, brass and aluminium.

The foaming action ensures the lubricant rapidly penetrates to the cutting edges without running off the tool or workpiece and allows economical application, even in deep holes. This prolongs tool life and improves surface finish.

### Outstanding Features

- Extends tool life
- Improves surface finish
- Increases removal rates
- Reduces production costs

### Directions for use

ROCOL RTD Foamcut should be shaken well before use then sprayed directly onto the tool or workpiece from a distance of 15 - 30 cm. The direction control straw allows greater accessibility to difficult operations and enables application exactly where needed. Ensure adequate ventilation.

### Technical Data

<i>Appearance</i>	: Creamy-white foam
<i>Odour</i>	: Mild
<i>Solvents</i>	: None
<i>Nitrites</i>	: None
<i>Silicones</i>	: None
<i>Storage</i>	: Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
<i>Pack Sizes</i>	: 300ml

continued.....

#### ROCOL Limited

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

RTD Foamcut

## Health and Safety

Further Technical Data and Health and Safety information (COSHH, MSDS) is available from the Customer Service Department, ROCOL Ltd., ROCOL House, Swillington, Leeds, LS26 8BS, England.

**Telephone:** 0113 232 2700, (When calling from outside UK: 44 113 232 2700);

**Fax:** 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: 5304a 23/02/96

### **ROCOL Limited**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9002 registered company.

ROCOL is a trade mark of ROCOL Limited.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.