



Part Number: A0284798

50 PAIRS BIX MOUNT

Product Description

50 PAIRS BIX MOUNT

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	IBDN System 1200

Physical Characteristics (Overall)

Insulation

Nominal Wall Thickness
0.034 in

Outer Jacket Material

Nominal Diameter	Nominal Wall Thickness
0.035 mm	0.035 mm

Port Count:	50 PAIRS (2 connectors, 25 pairs)
Packaging:	Individually packaged in a cardboard box
Weight:	1.2(g)

Applicable Standards & Environmental Programs

EU Directive Compliance:	EU Directive 2002/95/EC (RoHS)
EU RoHS Compliance Date (yyyy-mm-dd):	2008-01-30
Telecommunications Standards:	ANSI/TIA/EIA 568 C.2 Category 5e

Standards

ANSI/TIA Category:	N/A
--------------------	-----

Safety

Safety Listing:	ACA, UL 1863 and CSA-C22.2
-----------------	----------------------------

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Mechanical Characteristics

Storage Temp Range:	-40°C To +70°C
Installation Temp Range:	-10°C To +60°C
Operating Temp Range:	-10°C To +60°C
Tool Compatibility:	BIX Connecting Tool (A0270165)

Temperature Range

Dimensions

Width	Height	Depth
7.63	2.132	3.225

Part Number

Related Parts:	BIX CONNECTORS, DISTRIBUTION RING, MANAGEMENT MODULE, BIX PATCH COORD
----------------	---

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.