

156-01726

Article Number: 156-01726

Description: Blind Hole Mount Cable Tie for 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bag



Base Data	Local Order Number	156-01726
	Type	T50RBHMB
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Delivers high extraction force for reliable performance, yet it's easy to install.</li> <li>• Reusable fastener can be removed from threaded or nonthreaded holes using a 5/16" hex driver.</li> <li>• Heat stabilized material provides excellent resistance to high temperatures.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton Blind Hole Mount Cable Ties for threaded and nonthreaded holes offer an easy-to-use method for bundling and affixing cables. The two-piece design includes a heat stabilized cable tie and formula-matched, 1/4" mount that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or nonthreaded blind holes. Mount can slide along cable tie to adjust orientation if needed. Fastener can be removed from hole using a hex driver. This ensures fastener can be reused.
	GLOBAL PART NAME (auto set)	T50RBHMB-PA66HS-BK
	Short Description	Blind Hole Mount Cable Tie for 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bag
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225.0N
Length L (Imperial)		8.0"
Length L (Metric)		203.2mm
Fixing Hole Depth Min. (Imperial)		0.5"
Fixing Hole Depth Min. (Metric)		12.7mm
Identification Plate Position		none
Width W (Imperial)		0.31"
Width W (Metric)		7.8mm
Height H (Imperial)		0.736"
Height H (Metric)		18.7mm

156-01726



Product Dimensions	Height H2 (Imperial)	0.488"
	Height H2 (Metric)	12.4mm
	Bundle Diameter Min. (Imperial)	0.10"
	Bundle Diameter Min. (Metric)	2.5mm
	Bundle Diameter Max. (Imperial)	1.97"
	Bundle Diameter Max. (Metric)	50.0mm
	Diameter D (imperial)	0.25"
	Diameter D (metric)	6.0mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500