

156-01807

HellermannTyton

Article Number: 156-01807

Description: Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 6", 50lb, PA66HS, Black, 500/bag



Base Data	
Local Order Number	156-01807
Type	T50SOSBHMB
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Delivers high extraction force for reliable performance, yet it's easy to install. • Reusable fastener can be removed from threaded or nonthreaded holes using a 5/16" hex driver. • Heat stabilized material provides excellent resistance to high temperatures.
Quantity Per	bag
Product Description	HellermannTyton Blind Hole Mount Cable Ties for threaded and nonthreaded holes offer an easy-to-use method for bundling and affixing cables. The two-piece design includes a heat stabilized cable tie and formula-matched, 1/4" mount that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or nonthreaded blind holes. Mount can slide along cable tie to adjust orientation if needed. Fastener can be removed from hole using a hex driver. This ensures fastener can be reused.
GLOBAL PART NAME (auto set)	T50SOSBHMB-PA66HS-BK
Short Description	Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 6", 50lb, PA66HS, Black, 500/bag
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225.0N
Length L (Imperial)	6.0"
Length L (Metric)	150.0mm
Fixing Hole Depth Min. (Imperial)	0.5"
Fixing Hole Depth Min. (Metric)	12.7mm
Identification Plate Position	none
Width W (Imperial)	0.31"
Width W (Metric)	7.8mm
Height H (Imperial)	0.736"
Height H (Metric)	18.7mm

156-01807



Product Dimensions	Height H2 (Imperial)	0.488"
	Height H2 (Metric)	12.4mm
	Bundle Diameter Min. (Imperial)	0.10"
	Bundle Diameter Min. (Metric)	2.5mm
	Bundle Diameter Max. (Imperial)	1.40"
	Bundle Diameter Max. (Metric)	35.0mm
	Diameter D (imperial)	0.25"
	Diameter D (metric)	6.0mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500