## TECHNICAL DATA SHEET



## LAN Cable Model: CB11324

## RoHS Compliant

Design of cable:	
Inner conductor	Single bare copper 0.485mm dia ±0.005mm
Insulation	HDPE
Insulation Dia	0.85mm dia ±0.05mm
Core colours	WH-BU/BU WH-OG/OG WH-GN/GN WH-BN/BN
Jacket	PVC
Colour	Blue
Size	4.8mm dia ±0.2mm
Wall thickness	≈0.5mm
Printing	By request
Electric data at 20°C	
Conductor resistance	<110Ω/km
Insulation resistance	>5000MΩ/km
Testing voltage	wire/wire 50Hz 1min=1.5KV
Impedance	100Ω ±15Ω
Packing	305M/CTN
Temperature range	-10°C ~ 60°C

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

