



## Main

Range	TeSys
Product name	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Motor control Resistive load
Utilisation category	AC-1 AC-3 AC-4
Poles description	3P
Pole contact composition	3 NO
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	275 A (<= 40 °C) at <= 440 V AC AC-1 185 A (<= 55 °C) at <= 440 V AC AC-3
Motor power kW	90 kW at 380...400 V AC 50/60 Hz AC-3 100 kW at 415 V AC 50/60 Hz AC-3 100 kW at 440 V AC 50/60 Hz AC-3 110 kW at 500 V AC 50/60 Hz AC-3 110 kW at 660...690 V AC 50/60 Hz AC-3 100 kW at 1000 V AC 50/60 Hz AC-3 33 kW at 400 V AC 50/60 Hz AC-4 55 kW at 220...240 V AC 50/60 Hz AC-3

## Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overtension category	III
[Ith] conventional free air thermal current	275 A at <= 40 °C
Irms rated making capacity	1850 A AC conforming to IEC 60947-4-1
Rated breaking capacity	1480 A conforming to IEC 60947-4-1

[Icw] rated short-time withstand current	1500 A <= 40 °C 10 s 920 A <= 40 °C 30 s 740 A <= 40 °C 1 min 500 A <= 40 °C 3 min 400 A <= 40 °C 10 min
Associated fuse rating	200 A aM at <= 440 V 315 A gG at <= 440 V
Average impedance	0.33 mOhm at 50 Hz - Ith 275 A
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power dissipation per pole	12 W AC-3 25 W AC-1
Mounting support	Plate
Standards	EN 60947-1 IEC 60947-4-1 IEC 60947-1 JIS C8201-4-1 EN 60947-4-1
Product certifications	LROS (Lloyds register of shipping) BV UL DNV RINA CB ABS CSA RMRoS
Connections - terminals	Power circuit : connector 1 cable(s) 150 mm <sup>2</sup> Power circuit : lugs-ring terminals 1 cable(s) 150 mm <sup>2</sup> Power circuit : bolted connection Power circuit : bar 2 x (25 x 3 mm)
Tightening torque	Power circuit : 18 N.m

## Environment

IP degree of protection	IP2x front face with shrouds (ordered separately) conforming to IEC 60529 IP2x front face with shrouds (ordered separately) conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-40...70 °C
Operating altitude	3000 m without derating in temperature
Mechanical robustness	Vibrations contactor closed 5 Gn, 5...300 Hz Shocks contactor open 7 Gn for 11 ms Vibrations contactor open 2 Gn, 5...300 Hz Shocks contactor closed 15 Gn for 11 ms
Height	174 mm
Width	168.5 mm
Depth	181 mm
Product weight	5.45 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0843 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---