DISCLAMER: AL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED LIPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH,			ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINE		Picture for Refer	TECHNOLOGY		
TOLERANCES: UNLESS DTHERVISE SPECIFIEDS DIMENSIONS ARE FOR REFERENCE PURPOSES DNLY.				DIN Rail Sold Separately 63.2	Picture for Reference only, color is Beige	SPC-FOD&DWG	WHELHER IN WHOLE OR IN PART CAN BE REPROSAGED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.	- RIGHTS RESERVED. NO PORTION OF T
Jason Nash	Jason Nash	CHECKED BY:	Jeff McVicker	· · · · · · · · · · · · · · · · · · ·	ש		OF SPC	HIS PUBLICATION.
	2			45.0		1847	DCP #	
03/24/08	03/24/08	DATE:	7/18/05	49 0 0		>	REV	-
B SCALE: NTS	Δ	SIZE DWC. NO.	URAWING TITLE:	Voltage Rating: 300 Volts Amperage: 6.3 Amps AWG: 26 ~ 8		Raleased	DESCRIPTION	REVISIONS
U.0	SPC11912			rage 26 R				
U.O.M.: Millimeters	2		Fuse	∼ 8. 8.	·	UW M	DRAWN	
ieters			Block	ω <u>φ</u> ≥ω		7/18/05		DOD. NO. SPC-FDOS
	83	ELECT		mp 00		Ľ	CHECKD	•
SHEET:	83C7600.dwg	ELECTRONIC FILE		° <olt< td=""><td></td><td>03/24/08</td><td>DATE</td><td>Effective: 7/8/02</td></olt<>		03/24/08	DATE	Effective: 7/8/02
-).dwg	Ē		ίΩ.		٦N	APPRVD	÷
우 -	⊳	REV				03/24/08	DATE	DCP Nov 1308