



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 22

Loctite 278 50ml, Cz/Sk

SDS No. : 173002
V010.0

Revision: 30.06.2016

printing date: 23.01.2018

Replaces version from: 30.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 278 50ml, Cz/Sk

Contains:

2-Propenoic acid, 2-methyl-, (octahydro-4,7-methano-1H-indene-5-diyl)bis(methylene) ester
Hydroxypropyl methacrylate
Methacryloyloxyethyl succinate
2,2'-Ethylenedioxydiethyl dimethacrylate
2-Hydroxyethyl methacrylate
Acetic acid, 2-phenylhydrazide
Benzenamine, N,N,4-trimethyl-, N-oxide
Maleic acid
Hydroxyethyl methacrylate phosphate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|--|------------|
| Skin irritation | Category 2 |
| H315 Causes skin irritation. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Skin sensitizer | Category 1 |
| H317 May cause an allergic skin reaction. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation. | |
| Target organ: respiratory tract irritation | |

2.2. Label elements

Label elements (CLP):

| | |
|--|--|
| Hazard pictogram: |  |
| Signal word: | Warning |
| Hazard statement: | H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. |
| Precautionary statement: | ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements*** |
| Precautionary statement: Prevention | P261 Avoid breathing vapours. P280 Wear protective gloves. |
| Precautionary statement: Response | P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. |

2.3. Other hazards

Non corrosive to eyes according to test method OECD 438 or based on analogy to similar products tested.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:
Anaerobic Sealant

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---|-------------------------------|------------|--|
| 2-Propenoic acid, 2-methyl-, (octahydro-4,7-methano-1H-indene-5-diyl)bis(methylene) ester 43048-08-4 | 256-062-6 | 10- 20 % | STOT SE 3 H335 Skin Irrit. 2 H315 Eye Irrit. 2 H319 |
| Hydroxypropyl methacrylate 27813-02-1 | 248-666-3 01-2119490226-37 | 5- < 10 % | Skin Sens. 1 H317 Eye Irrit. 2 H319 |
| Methacryloyloxyethyl succinate 20882-04-6 | 244-096-4 | 5- < 10 % | Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Dam. 1 H318 |
| 2,2'-Ethylendioxydiethyl dimethacrylate 109-16-0 | 203-652-6 01-2119969287-21 | 1- < 3 % | Skin Sens. 1B H317 |
| Cumene hydroperoxide 80-15-9 | 201-254-7 | 1- < 2,5 % | Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314 |
| 2-Hydroxyethyl methacrylate 868-77-9 | 212-782-2 01-2119490169-29 | 0,1- < 1 % | Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 |
| Acetic acid, 2-phenylhydrazide 114-83-0 | 204-055-3 | 0,1- < 1 % | Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351 |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | 424-440-1 01-0000017090-82 | 0,1- < 1 % | Skin Sens. 1; Dermal H317 Muta. 2 H341 |
| Tributyl amine 102-82-9 | 203-058-7 01-2119474898-14 | 0,1- < 1 % | Acute Tox. 4; Oral H302 Acute Tox. 2; Dermal H310 Skin Irrit. 2 H315 Acute Tox. 1; Inhalation H330 |
| Maleic acid | 203-742-5 | 0,1- < 1 % | Acute Tox. 4; Oral |

| | | | |
|---|-------------------------------|---------------|--|
| 110-16-7 | 01-2119488705-25 | | H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335 |
| Methacrylic acid 79-41-4 | 201-204-4 01-2119463884-26 | 0,1- < 1 % | Acute Tox. 4; Oral H302 Acute Tox. 3; Dermal H311 Acute Tox. 4; Inhalation H332 Skin Corr. 1A H314 |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | 258-053-2 | 0,1- < 1 % | Skin Corr. 1C H314 Skin Sens. 1 H317 |
| Hydroquinone 123-31-9 | 204-617-8 01-2119524016-51 | 0,01- < 0,1 % | Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Carc. 2 H351 Muta. 2 H341 Acute Tox. 4; Oral H302 Eye Dam. 1 H318 Skin Sens. 1 H317 M factor (Acute Aquat Tox): 10 |

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Cumene 98-82-8 [CUMENE] | 50 | 250 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | | | Skin designation: | Can be absorbed through the skin. | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | 25 | 125 | Time Weighted Average (TWA): | | EH40 WEL |
| Cumene 98-82-8 [CUMENE] | 50 | 250 | Short Term Exposure Limit (STEL): | Indicative | ECTLV |
| Cumene 98-82-8 [CUMENE] | 20 | 100 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 40 | 143 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 20 | 72 | Time Weighted Average (TWA): | | EH40 WEL |
| Hydroquinone 123-31-9 [HYDROQUINONE] | | 0,5 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Cumene 98-82-8 [ISOPROPYL BENZENE] | 20 | 100 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Cumene 98-82-8 [ISOPROPYL BENZENE] | 50 | 250 | Short Term Exposure Limit (STEL): | Indicative OELV | IR_OEL |
| Cumene 98-82-8 [ISOPROPYL BENZENE] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |
| Cumene 98-82-8 [CUMENE] | 50 | 250 | Short Term Exposure Limit (STEL): | Indicative | ECTLV |
| Cumene 98-82-8 [CUMENE] | 20 | 100 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 20 | 70 | Time Weighted Average (TWA): | | IR_OEL |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 40 | 140 | Short Term Exposure Limit (STEL): | | IR_OEL |
| Hydroquinone 123-31-9 [HYDROQUINONE] | | 0,5 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------|-----------------|-------|-----|--------------|--------------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | aqua (freshwater) | | | | | 0,904 mg/L | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | aqua (marine water) | | | | | 0,904 mg/L | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | sewage treatment plant (STP) | | | | | 10 mg/L | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | aqua (intermittent releases) | | | | | 0,972 mg/L | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | sediment (freshwater) | | | | 6,28 mg/kg | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | sediment (marine water) | | | | 6,28 mg/kg | | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | soil | | | | 0,727 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (freshwater) | | | | | 0,164 mg/L | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (marine water) | | | | | 0,0164 mg/L | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sewage treatment plant (STP) | | | | | 10 mg/L | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (intermittent releases) | | | | | 0,164 mg/L | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sediment (freshwater) | | | | 1,85 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sediment (marine water) | | | | 0,185 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | soil | | | | 0,274 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (freshwater) | | | | | 0,0031 mg/L | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | | | | 0,00031 mg/L | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | | | | 0,031 mg/L | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Sewage treatment plant | | | | | 0,35 mg/L | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | soil | | | | 0,0029 mg/kg | | |
| 2-Hydroxyethyl methacrylate 868-77-9 | aqua (freshwater) | | | | | 0,482 mg/L | |
| 2-Hydroxyethyl methacrylate 868-77-9 | aqua (marine water) | | | | | 0,482 mg/L | |
| 2-Hydroxyethyl methacrylate 868-77-9 | sewage treatment plant (STP) | | | | | 10 mg/L | |
| 2-Hydroxyethyl methacrylate 868-77-9 | aqua (intermittent releases) | | | | | 1 mg/L | |
| 2-Hydroxyethyl methacrylate 868-77-9 | sediment (freshwater) | | | | 3,79 mg/kg | | |

| | | | | | | | |
|---|------------------------------------|--|--|--|-----------------|--------------|--|
| 2-Hydroxyethyl methacrylate 868-77-9 | sediment (marine water) | | | | 3,79 mg/kg | | |
| 2-Hydroxyethyl methacrylate 868-77-9 | soil | | | | 0,476 mg/kg | | |
| Tributyl amine 102-82-9 | aqua (freshwater) | | | | | 0,0036 mg/L | |
| Tributyl amine 102-82-9 | aqua (marine water) | | | | | 0,00036 mg/L | |
| Tributyl amine 102-82-9 | sediment (freshwater) | | | | 16,9 mg/kg | | |
| Tributyl amine 102-82-9 | sediment (marine water) | | | | 1,69 mg/kg | | |
| Tributyl amine 102-82-9 | aqua (intermittent releases) | | | | | 0,036 mg/L | |
| Tributyl amine 102-82-9 | soil | | | | 3,37 mg/kg | | |
| Tributyl amine 102-82-9 | sewage treatment plant (STP) | | | | | 100 mg/L | |
| Maleic acid 110-16-7 | aqua (freshwater) | | | | | 0,1 mg/L | |
| Maleic acid 110-16-7 | aqua (intermittent releases) | | | | | 0,4281 mg/L | |
| Maleic acid 110-16-7 | sediment (freshwater) | | | | 0,334 mg/kg | | |
| Maleic acid 110-16-7 | sewage treatment plant (STP) | | | | | 44,6 mg/L | |
| Maleic acid 110-16-7 | aqua (marine water) | | | | | 0,01 mg/L | |
| Maleic acid 110-16-7 | sediment (marine water) | | | | 0,0334 mg/kg | | |
| Maleic acid 110-16-7 | soil | | | | 0,0415 mg/kg | | |
| Methacrylic acid 79-41-4 | aqua (freshwater) | | | | | 0,82 mg/L | |
| Methacrylic acid 79-41-4 | aqua (marine water) | | | | | 0,82 mg/L | |
| Methacrylic acid 79-41-4 | sewage treatment plant (STP) | | | | | 10 mg/L | |
| Methacrylic acid 79-41-4 | aqua (intermittent releases) | | | | | 0,82 mg/L | |
| Methacrylic acid 79-41-4 | soil | | | | 1,2 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (freshwater) | | | | | 0,114 µg/L | |
| Hydroquinone 123-31-9 | aqua (marine water) | | | | | 0,0114 µg/L | |
| Hydroquinone 123-31-9 | sediment (freshwater) | | | | | 0,98 µg/kg | |
| Hydroquinone 123-31-9 | sediment (marine water) | | | | | 0,097 µg/kg | |
| Hydroquinone 123-31-9 | aqua (intermittent releases) | | | | | 0,00134 mg/L | |
| Hydroquinone 123-31-9 | soil | | | | | 0,129 µg/kg | |
| Hydroquinone 123-31-9 | sewage treatment plant (STP) | | | | | 0,71 mg/L | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|--|---------------|-------------------------|---------|
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Workers | dermal | Long term exposure - systemic effects | | 4,2 mg/kg bw/day | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | Workers | Inhalation | Long term exposure - systemic effects | | 14,7 mg/m ³ | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | general population | dermal | Long term exposure - systemic effects | | 2,5 mg/kg bw/day | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | general population | Inhalation | Long term exposure - systemic effects | | 8,8 mg/m ³ | |
| Methacrylic acid, monoester with propane-1,2-diol 27813-02-1 | general population | oral | Long term exposure - systemic effects | | 2,5 mg/kg bw/day | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Workers | inhalation | Long term exposure - systemic effects | | 48,5 mg/m ³ | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Workers | dermal | Long term exposure - systemic effects | | 13,9 mg/kg bw/day | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | general population | inhalation | Long term exposure - systemic effects | | 14,5 mg/m ³ | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | general population | dermal | Long term exposure - systemic effects | | 8,33 mg/kg bw/day | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | general population | oral | Long term exposure - systemic effects | | 8,33 mg/kg bw/day | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m ³ | |
| 2-Hydroxyethyl methacrylate 868-77-9 | Workers | dermal | Long term exposure - systemic effects | | 1,3 mg/kg bw/day | |
| 2-Hydroxyethyl methacrylate 868-77-9 | Workers | Inhalation | Long term exposure - systemic effects | | 4,9 mg/m ³ | |
| 2-Hydroxyethyl methacrylate 868-77-9 | general population | dermal | Long term exposure - systemic effects | | 0,83 mg/kg bw/day | |
| 2-Hydroxyethyl methacrylate 868-77-9 | general population | Inhalation | Long term exposure - systemic effects | | 2,9 mg/m ³ | |
| 2-Hydroxyethyl methacrylate 868-77-9 | general population | oral | Long term exposure - systemic effects | | 0,83 mg/kg bw/day | |
| Tributyl amine 102-82-9 | Workers | inhalation | Long term exposure - systemic effects | | 15,2 mg/m ³ | |
| Tributyl amine 102-82-9 | Workers | inhalation | Long term exposure - local effects | | 15,2 mg/m ³ | |
| Maleic acid 110-16-7 | Workers | dermal | Acute/short term exposure - local effects | | 0,55 mg/cm ² | |
| Maleic acid 110-16-7 | Workers | dermal | Long term exposure - local effects | | 0,04 mg/cm ² | |
| Maleic acid 110-16-7 | Workers | dermal | Acute/short term exposure - systemic effects | | 58 mg/kg bw/day | |
| Maleic acid 110-16-7 | Workers | dermal | Long term exposure - systemic effects | | 3,3 mg/kg bw/day | |
| Maleic acid 110-16-7 | Workers | inhalation | Acute/short term exposure - local effects | | 3 mg/m ³ | |
| Maleic acid 110-16-7 | Workers | inhalation | Long term exposure - | | 3 mg/m ³ | |

| | | | | | |
|-----------------------------|-----------------------|------------|--|--|------------------------|
| | | | systemic effects | | |
| Maleic acid 110-16-7 | Workers | inhalation | Long term exposure - local effects | | 3 mg/m ³ |
| Maleic acid 110-16-7 | Workers | inhalation | Acute/short term exposure - systemic effects | | 3 mg/m ³ |
| Methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - local effects | | 88 mg/m ³ |
| Methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - systemic effects | | 29,6 mg/m ³ |
| Methacrylic acid 79-41-4 | Workers | dermal | Long term exposure - systemic effects | | 4,25 mg/kg bw/day |
| Methacrylic acid 79-41-4 | general population | Inhalation | Long term exposure - local effects | | 6,55 mg/m ³ |
| Methacrylic acid 79-41-4 | general population | Inhalation | Long term exposure - systemic effects | | 6,3 mg/m ³ |
| Methacrylic acid 79-41-4 | general population | dermal | Long term exposure - systemic effects | | 2,55 mg/kg bw/day |
| Hydroquinone 123-31-9 | Workers | dermal | Long term exposure - systemic effects | | 128 mg/kg bw/day |
| Hydroquinone 123-31-9 | Workers | Inhalation | Long term exposure - systemic effects | | 7 mg/m ³ |
| Hydroquinone 123-31-9 | Workers | Inhalation | Long term exposure - local effects | | 1 mg/m ³ |
| Hydroquinone 123-31-9 | general population | dermal | Long term exposure - systemic effects | | 64 mg/kg bw/day |
| Hydroquinone 123-31-9 | general population | Inhalation | Long term exposure - systemic effects | | 1,74 mg/m ³ |
| Hydroquinone 123-31-9 | general population | Inhalation | Long term exposure - local effects | | 0,5 mg/m ³ |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|------------------------------------|
| Appearance | liquid green |
| Odor | characteristic |
| Odour threshold | No data available / Not applicable |
| pH | No data available / Not applicable |
| Initial boiling point | > 149 °C (> 300.2 °F) |
| Flash point | > 100 °C (> 212 °F) |
| Decomposition temperature | No data available / Not applicable |
| Vapour pressure (50 °C (122 °F)) | < 300 mbar |
| Density (20 °C (68 °F)) | 1,1 - 1,14 g/cm ³ |
| Bulk density | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Solubility (qualitative) (Solvent: Water) | Insoluble |
| Solidification temperature | No data available / Not applicable |
| Melting point | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Evaporation rate | No data available / Not applicable |
| Vapor density | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

STOT-single exposure:

May cause respiratory irritation.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Non corrosive to eyes according to test method OECD 438 or based on analogy to similar products tested.

Sensitizing:

May cause an allergic skin reaction.

Acute oral toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|--|---------------|---------------|-------------------------|------------------|---------|---|
| Hydroxypropyl methacrylate 27813-02-1 | LD50 | > 2.000 mg/kg | oral | | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Methacryloyloxyethyl succinate 20882-04-6 | LD50 | > 2.000 mg/kg | oral | | rat | OECD Guideline 423 (Acute Oral toxicity) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | LD50 | 10.837 mg/kg | oral | | rat | |
| Cumene hydroperoxide 80-15-9 | LD50 | 550 mg/kg | oral | | rat | |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | LD50 | > 2.000 mg/kg | oral | | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Tributyl amine 102-82-9 | LD50 | 320 mg/kg | oral | | mouse | |
| Tributyl amine 102-82-9 | LD50 | 420 mg/kg | | | rat | Not specified |
| Maleic acid 110-16-7 | LD50 | 708 mg/kg | oral | | rat | |
| Methacrylic acid 79-41-4 | LD50 | 1.320 mg/kg | oral | | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | LD50 | > 2.000 mg/kg | oral | | rat | OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) |
| Hydroquinone 123-31-9 | LD50 | 367 mg/kg | oral | | rat | OECD Guideline 401 (Acute Oral Toxicity) |

Acute inhalative toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|---------------|------------|-------------------------|------------------|---------|--|
| Tributyl amine 102-82-9 | LC50 | 0,5 mg/l | vapour | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Methacrylic acid 79-41-4 | LC50 | > 3,6 mg/l | aerosol | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |

Acute dermal toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|--|-------------------------------|---------------------|-------------------------|------------------|---------|---------------------------|
| Hydroxypropyl methacrylate 27813-02-1 | LD50 | > 5.000 mg/kg | dermal | | rabbit | |
| Cumene hydroperoxide 80-15-9 | LD50 | 1.200 - 1.520 mg/kg | dermal | | | |
| 2-Hydroxyethyl methacrylate 868-77-9 | LD50 | > 3.000 mg/kg | dermal | | rabbit | |
| Tributyl amine 102-82-9 | LD50 | 195 mg/kg | dermal | | rabbit | Not specified |
| Maleic acid 110-16-7 | LD50 | 1.560 mg/kg | dermal | | rabbit | |
| Methacrylic acid 79-41-4 | Acute toxicity estimate (ATE) | 500 mg/kg | dermal | | | Expert judgement |
| Methacrylic acid 79-41-4 | LD50 | 500 - 1.000 mg/kg | | | rabbit | Dermal Toxicity Screening |

Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|--|-------------------------|------------------|--|--|
| Methacryloyloxyethyl succinate 20882-04-6 | not irritating | 0,25 h | Human, EPISKIIN™ Reconstituted Human Epidermis model | OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method) |
| Methacryloyloxyethyl succinate 20882-04-6 | Not Classified | 4 h | Human, EPISKIIN™ Reconstituted Human Epidermis model | OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method) |
| Cumene hydroperoxide 80-15-9 | corrosive | | rabbit | Draize Test |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | slightly irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Maleic acid 110-16-7 | irritating | 24 h | human | Patch Test |
| Methacrylic acid 79-41-4 | Category 1A (corrosive) | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | corrosive | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|--|---------------------|------------------|---------|---|
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | slightly irritating | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | slightly irritating | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Maleic acid 110-16-7 | highly irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Methacrylic acid 79-41-4 | Category I | | rabbit | Draize Test |

Respiratory or skin sensitization:

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|--|-----------------|-------------------------------------|------------|---|
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | not sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Maleic acid 110-16-7 | sensitising | Mouse local lymph node assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Maleic acid 110-16-7 | sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Methacrylic acid 79-41-4 | not sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Hydroquinone 123-31-9 | sensitising | Guinea pig maximisation test | guinea pig | |

Germ cell mutagenicity:

| Hazardous components CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--|---------|--|
| Methacryloyloxyethyl succinate 20882-04-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Cumene hydroperoxide 80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Cumene hydroperoxide 80-15-9 | negative | dermal | | mouse | |
| 2-Hydroxyethyl methacrylate 868-77-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| | positive | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | positive | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Maleic acid 110-16-7 | negative | bacterial reverse mutation assay (e.g Ames test) | no data | | Ames Test |
| | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Methacrylic acid 79-41-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Methacrylic acid 79-41-4 | negative | inhalation | | mouse | OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Hydroquinone 123-31-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | EU Method B.13/14 (Mutagenicity) |

Carcinogenicity:

| Hazardous components CAS-No. | Result | Species | Sex | Exposure time Frequency of treatment | Route of application | Method |
|---------------------------------|------------------|---------|-------------|---|-------------------------|--|
| Maleic acid 110-16-7 | not carcinogenic | rat | male/female | 2 y daily | oral: feed | OECD Guideline 451 (Carcinogenicity Studies) |

Reproductive toxicity:

| Hazardous substances CAS-No. | Result / Classification | Species | Exposure time | Species | Method |
|---------------------------------|---|--|------------------|---------|--|
| Maleic acid 110-16-7 | NOAEL F1 = 150 mg/kg NOAEL F2 = 55 mg/kg | Two generation study oral: gavage | min. 80 d | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |

Repeated dose toxicity

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---------------------------------|-----------------------|-------------------------|--|---------|--|
| Cumene hydroperoxide 80-15-9 | | inhalation: aerosol | 6 h/d5 d/w | rat | |
| Maleic acid 110-16-7 | NOAEL=>= 40 mg/kg | oral: feed | 90 ddaily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Hydroquinone 123-31-9 | NOAEL=>= 250 mg/kg | oral: gavage | 14 days5 days/week. 12 doses | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| Hydroquinone 123-31-9 | LOAEL=<= 500 mg/kg | oral: gavage | 14 days5 days/week. 12 doses | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|---|---------------|--------------|----------------------------|------------------|--|---|
| Hydroxypropyl methacrylate 27813-02-1 | LC50 | 493 mg/l | Fish | 48 h | Leuciscus idus melanotus | DIN 38412-15 |
| Hydroxypropyl methacrylate 27813-02-1 | EC50 | > 130 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroxypropyl methacrylate 27813-02-1 | EC10 | 1.140 mg/l | Bacteria | 16 h | | |
| Methacryloyloxyethyl succinate 20882-04-6 | EC50 | > 515,4 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | EC50 | > 312 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | LC50 | 16,4 mg/l | Fish | 96 h | | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Cumene hydroperoxide 80-15-9 | LC50 | 3,9 mg/l | Fish | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 18 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Cumene hydroperoxide 80-15-9 | ErC50 | 3,1 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | EC10 | 70 mg/l | Bacteria | 30 min | | |
| 2-Hydroxyethyl methacrylate 868-77-9 | LC50 | 227 mg/l | Fish | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | EC50 | 380 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | EC50 | 345 mg/l | Algae | 72 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| | NOEC | 160 mg/l | Algae | 72 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | EC0 | > 3.000 mg/l | Bacteria | 16 h | | |
| 2-Hydroxyethyl methacrylate 868-77-9 | NOEC | 24,1 mg/l | chronic Daphnia | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Benzenamine, N,N,4- trimethyl-, N-oxide 825-85-4 | LC50 | 460 mg/l | Fish | 96 h | Brachydanio rerio (new name: Danio rerio) | |
| Benzenamine, N,N,4- trimethyl-, N-oxide 825-85-4 | EC0 | 821 mg/l | Bacteria | 16 h | | |
| Tributyl amine 102-82-9 | LC50 | 60,2 mg/l | Fish | 48 h | Leuciscus idus | DIN 38412-15 |
| Tributyl amine 102-82-9 | EC50 | 8 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Tributyl amine 102-82-9 | EC10 | 1,378 mg/l | Algae | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| | EC50 | 8,215 mg/l | Algae | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Tributyl amine 102-82-9 | EC0 | > 800 mg/l | Bacteria | 3 h | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

| | | | | | | |
|--|-------|-------------|--------------------|--------|--|---|
| Maleic acid 110-16-7 | LC50 | > 245 mg/l | Fish | 48 h | Leuciscus idus | DIN 38412-15 |
| Maleic acid 110-16-7 | EC50 | 42,81 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Methacrylic acid 79-41-4 | LC50 | 85 mg/l | Fish | 96 h | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| Methacrylic acid 79-41-4 | EC50 | > 130 mg/l | Daphnia | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| Methacrylic acid 79-41-4 | NOEC | 8,2 mg/l | Algae | 72 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Methacrylic acid 79-41-4 | EC50 | 45 mg/l | Algae | 72 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Methacrylic acid 79-41-4 | EC10 | 100 mg/l | Bacteria | 17 h | | |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | LC50 | > 112 mg/l | Fish | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | EC50 | 68 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | EC50 | > 120 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | NOEC | > 30 mg/l | Algae | 72 h | Pseudokirchnerella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroquinone 123-31-9 | LC50 | 0,638 mg/l | Fish | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hydroquinone 123-31-9 | EC50 | 0,134 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroquinone 123-31-9 | EC50 | 0,335 mg/l | Algae | 72 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroquinone 123-31-9 | EC 50 | 0,038 mg/l | Bacteria | 30 min | | |
| Hydroquinone 123-31-9 | NOEC | 0,0057 mg/l | chronic Daphnia | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

| Hazardous components CAS-No. | Result | Route of application | Degradability | Method |
|---------------------------------|--------|-------------------------|---------------|--------|
|---------------------------------|--------|-------------------------|---------------|--------|

| | | | | |
|--|--|---------|------------|--|
| Hydroxypropyl methacrylate 27813-02-1 | readily biodegradable | aerobic | 94,2 % | OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | readily biodegradable, but failing 10-day window | aerobic | 80 % | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | readily biodegradable | | 85 % | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Cumene hydroperoxide 80-15-9 | | no data | 0 % | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | readily biodegradable | aerobic | 92 - 100 % | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| Benzenamine, N,N,4-trimethyl-, N-oxide 825-85-4 | | aerobic | 0 - 3 % | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |
| Tributyl amine 102-82-9 | | aerobic | < 10 % | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| | inherently biodegradable | aerobic | 94 % | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |
| | readily biodegradable | aerobic | 80,3 % | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Maleic acid 110-16-7 | readily biodegradable | aerobic | 97,08 % | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Methacrylic acid 79-41-4 | inherently biodegradable | aerobic | 100 % | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |
| | readily biodegradable | aerobic | 86 % | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | readily biodegradable | aerobic | 78,3 % | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Hydroquinone 123-31-9 | readily biodegradable | aerobic | 75 - 81 % | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

Cured adhesives are immobile.

Bioaccumulative potential:

No data available for the product.

| Hazardous components CAS-No. | LogKow | Bioconcentration factor (BCF) | Exposure time | Species | Temperature | Method |
|---------------------------------|--------|----------------------------------|------------------|---------|-------------|--------|
|---------------------------------|--------|----------------------------------|------------------|---------|-------------|--------|

| | | | | | | |
|--|---------------|-----|--|-------------|-------|--|
| Hydroxypropyl methacrylate 27813-02-1 | 0,97 | | | | | |
| Methacryloyloxyethyl succinate 20882-04-6 | 0,783 | | | | 23 °C | EU Method A.8 (Partition Coefficient) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | 1,88 | | | | | |
| Cumene hydroperoxide 80-15-9 | | 9,1 | | calculation | | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |
| Cumene hydroperoxide 80-15-9 | 2,16 | | | | | |
| Acetic acid, 2-phenylhydrazide 114-83-0 | 0,74 | | | | | |
| Tributyl amine 102-82-9 | 3,338 | | | | 25 °C | OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method) |
| Maleic acid 110-16-7 | -1,3 | | | | 20 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Methacrylic acid 79-41-4 | 0,93 | | | | 22 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Hydroxyethyl methacrylate phosphate 52628-03-2 | 1 - < 2,72 | | | | 30 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Hydroquinone 123-31-9 | 0,59 | | | | | EU Method A.8 (Partition Coefficient) |

12.5. Results of PBT and vPvB assessment

| Hazardous components CAS-No. | PBT/vPvB |
|--|---|
| Hydroxypropyl methacrylate 27813-02-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Cumene hydroperoxide 80-15-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2-Hydroxyethyl methacrylate 868-77-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Tributyl amine 102-82-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Maleic acid 110-16-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Methacrylic acid 79-41-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Hydroquinone 123-31-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.
Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H242 Heating may cause a fire.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.