

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 9

LOCTITE LB 8106 known as Loctite 8106 400g EGFD

SDS No. : 283266 V004.1 Revision: 02.06.2015 printing date: 06.12.2017 Replaces version from: 10.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE LB 8106 known as Loctite 8106 400g EGFD

- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Lubricant
- **1.3. Details of the supplier of the safety data sheet** Henkel Ltd Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Warning

Signal word:

Hazard statement:

H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.

Page 2 of 9

Precautionary statement: Prevention P273 Avoid release to the environment.

Precautionary statement: P337+P313 If eye irritation persists: Get medical advice/attention. **Response**

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Lubricant

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3	272-028-3	> 1-< 2,5 %	Aquatic Chronic 2 H411 Skin Irrit. 2 H315 Eye Dam. 1 H318
Butyl hydroxytoluene 128-37-0	204-881-4 01-2119480433-40 01-2119555270-46 01-2119565113-46	> 0,1-< 1%	Aquatic Acute 1 H400 Aquatic Chronic 1 H410

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Seek medical advice.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed Prolonged or repeated contact may cause skin irritation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Vapours should be extracted to avoid inhalation. Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place. Keep away from heat and direct sunlight.

7.3. Specific end use(s) Lubricant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ррт	mg/m ³	~ 1	Short term exposure limit category / Remarks	Regulatory list
2,6-di-tert-Butyl-p-cresol 128-37-0 [2,6-DI-TERT-BUTYL-P-CRESOL]		10	Time Weighted Average (TWA):		EH40 WEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental		Value				Remarks
	Compartment	period				r	
			mg/l	ppm	mg/kg	others	
2,6-Di-tert-butyl-p-cresol	soil					47,69 µg/kg	
128-37-0							
2,6-Di-tert-butyl-p-cresol	STP					0,17 mg/L	
128-37-0						_	
2,6-Di-tert-butyl-p-cresol	sediment					99,6 µg/kg	
128-37-0	(freshwater)						
2,6-Di-tert-butyl-p-cresol	oral				8,33 mg/kg		
128-37-0							
2,6-Di-tert-butyl-p-cresol	aqua (marine					0,0199 µg/L	
128-37-0	water)						
2,6-Di-tert-butyl-p-cresol	aqua					0,00199 mg/L	
128-37-0	(intermittent					_	
	releases)						
2,6-Di-tert-butyl-p-cresol	aqua					0,000199	
128-37-0	(freshwater)					mg/L	
2,6-Di-tert-butyl-p-cresol	sediment					9,96 µg/kg	
128-37-0	(marine water)						

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3	
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	Dermal	Long term exposure - systemic effects		0,5 mg/kg bw/day	
2,6-Di-tert-butyl-p-cresol 128-37-0	general population	inhalation	Long term exposure - systemic effects		0,86 mg/m3	
2,6-Di-tert-butyl-p-cresol 128-37-0	general population	Dermal	Long term exposure - systemic effects		0,25 mg/kg bw/day	
2,6-Di-tert-butyl-p-cresol 128-37-0	general population	oral	Long term exposure - systemic effects		0,25 mg/kg bw/day	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A

Hand protection: Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection: Wear protective glasses.

Skin protection: Wear suitable protective clothing.

SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties Appearance Grease light brown Odor characteristic Odour threshold No data available / Not applicable pН No data available / Not applicable Initial boiling point No data available / Not applicable No data available / Not applicable Flash point Decomposition temperature No data available / Not applicable No data available / Not applicable Vapour pressure 0,89 g/cm3 Density (20 °C (68 °F)) Bulk density No data available / Not applicable No data available / Not applicable Viscosity Viscosity (kinematic) No data available / Not applicable No data available / Not applicable Explosive properties Solubility (qualitative) Not miscible (Solvent: Water) Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable No data available / Not applicable Auto-ignition temperature Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties 9.2. Other information No data available / Not applicable

SECTION 10: Stability and reactivity

Page 6 of 9

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

Irritating organic vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

This material is considered to have low toxicity if swallowed. May cause irritation to the digestive tract.

Inhalative toxicity:

Due to the low volatility of the product there are no hazards associated with inhalation under normal conditions of use

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Phosphorodithioic acid, O.O-di-C1-14-alkyl	LD50	> 2.000 mg/kg	oral		rat	
esters, zinc salts 68649-42-3						
Butyl hydroxytoluene 128-37-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		

Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time	-	

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water. Harmful to aquatic life with long lasting effects.

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
DI 1 1'1' 1 0 0	LOSO	. 1 10 /1	Study			
Phosphorodithioic acid, O,O-	LC50	> 1 - 10 mg/l	Fish			OECD Guideline
di-C1-14-alkyl esters, zinc						203 (Fish, Acute
salts						Toxicity Test)
68649-42-3	5950				5.1.1	
Phosphorodithioic acid, O,O-	EC50	> 1 - 10 mg/l	Daphnia		Daphnia magna	OECD Guideline
di-C1-14-alkyl esters, zinc						202 (Daphnia sp.
salts						Acute
68649-42-3						Immobilisation
						Test)
Butyl hydroxytoluene	EC50	0,48 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
128-37-0						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Butyl hydroxytoluene	NOEC	0,316 mg/l	chronic	21 d	Daphnia magna	OECD 211
128-37-0		-	Daphnia		- •	(Daphnia magna,
			_			Reproduction Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Phosphorodithioic acid, O,O-		aerobic	5 %	OECD Guideline 301 D (Ready
di-C1-14-alkyl esters, zinc salts				Biodegradability: Closed Bottle Test)
68649-42-3				,
Butyl hydroxytoluene		aerobic	4,5 %	OECD Guideline 301 C (Ready
128-37-0				Biodegradability: Modified MITI
				Test (I))

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility:

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Butyl hydroxytoluene 128-37-0	5.1	330 - 1.800	8 weeks	Cyprinus carpio		OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Butyl hydroxytoluene 128-37-0	5,1					

12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	

Page 8 of 9

Butyl hydroxytoluene 128-37-0

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1.	UN number
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.2.	UN proper shipping name
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.3.	Transport hazard class(es)
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.4.	Packaging group
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.5.	Environmental hazards
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.6.	Special precautions for user
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.7.	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
	not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (1999/13/EC) < 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.