European Travel Adaptor





RoHS Compliant

Specifications

Base and Cover : FRPP
Socket Terminals (bus bar) : Brass
Plug Pin : Brass

Screw : Steel Zinc Plated
Shutter : Nylon (PA)
Voltage : 240V
Current Rating : 7.5A
Standard : BS5733

Conditions of use

- 1. Ambient temperature in the range -5°C to +40°C, the average value over 24 hours not exceeding 25°C.
- Situation not subject to exposure to direct radiation from the sun or other source of heat like to raise temperatures above the limits specified in 1.
- 3. Altitude not exceeding 2000 metres above sea level;
- 4. Atmosphere not subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions.

Part Number Table

Description	Part Number
European Travel Adaptor	PEL00518

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-ELEC is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.farnell.com www.cpc.co.uk

