PLA 3D Filament For 3D Printers



Specification

Print Temperature : 205°C ~ 225°C

Bed Temperature : No Heat / (60°C ~ 80°C)

Density : 1.24g/cm²)

Distortion Temperature : 52°C (0.45MPa)

Tensile Strength : 60MPa
Elongation at Break : 29%
Bending Strength : 87MPa

Part Number Table

Description	Part Number
PLA Filament, 1.75mm, Black, 1kg/Roll	MC002547
PLA Filament, 1.75mm, Green, 1kg/Roll	MC002548
PLA Filament, 1.75mm, Grey, 1kg/Roll	MC002549
PLA Filament, 1.75mm, Orange, 1kg/Roll	MC002550
PLA Filament, 1.75mm, Red, 1kg/Roll	MC002551
PLA Filament, 1.75mm, Silver, 1kg/Roll	MC002552
PLA Filament, 1.75mm, Blue, 1kg/Roll	MC002553
PLA Filament, 1.75mm, White, 1kg/Roll	MC002554
PLA Filament, 1.75mm, Yellow, 1kg/Roll	MC002555
PLA Filament, 1.75mm, Gold, 1kg/Roll	MC002556
PLA Filament, 1.75mm, Brown, 1kg/Roll	MC002557

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.



