

# Mini Anemometer



## Specifications

LCD Display	Dual line, 4-digit LCD
Sensor type	NTC
Operating Temperature	0 to 50°C (32°F to 122°F)
Storage Temperature	-10°C to 60°C (14°F to 140°F)
Operating Humidity	<80%RH
Storage Humidity	<80%RH
Bluetooth	Yes
Max / Min / AVG	Yes
Data Hold	Yes
Backlight	Yes
Low Battery Indicated	Yes
Auto Power Off	Yes
Disable Auto Power Off	Yes

Air Velocity	Range	Resolution	Accuracy
m/s (meter per second)	1.1 - 25m/s	0.01m/s	±(3% + 0.3m/s)
km/h (kilometers per hour)	4 - 90km/h	0.1km/h	±(3% + 1km/hr)
ft/min (feet per minute)	220 - 4920ft/min	1ft/min	±(3% + 40ft/m)
mph (miles per hour)	2.5 - 56mph	0.1mph	±(3% + 0.4mph)
Knots (nautical mph)	2.2 to 48 knots	0.1 knots	±(3% + 0.4 knots)
Air Temperature °C / °F	Range	Resolution	Accuracy
	-10°C to 60°C (14°F to 140°F)	0.1°C / 0.1°F	±2°C (4°F)

## Part Number Table

Description	Part Number
Mini Anemometer with Bluetooth	ST-90

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

