



Main

Range of product	Harmony XVS
Product or component type	Siren
Device short name	XVS
Colour	White
Signalling type	2 tones siren
[Us] rated supply voltage	12 V AC/DC 24 V AC/DC
Noise level	106 dB (continuous or intermittent tone) at 1 m

Complementary

Material	PC (body)
Product weight	0.8 kg
Marking	CE
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	500 mA 300 mA at 24 V
Clamping connection capacity	<= 1 x 1.5 mm ²
Electrical connection	Cable : 6.5...8.5 mm
Width	114 mm
Height	114 mm
Depth	153.2 mm
Compatibility code	XVS

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-30...50 °C
Electrical shock protection class	Class II conforming to EN/IEC 61140
IP degree of protection	IP53 conforming to EN/IEC 60529

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0808 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------

Siren

Dimensions

