

GP500 Gap Pad

GP500 is a silicone, thermally conductive material for use at a thermal interface. GP500 is specifically developed as a low thermal resistance gap pad.

- Works well under low pressure
- Good thermal conductivity; 5.0 W/m.K
- Excellent electrical insulation
- High heat dissipation; low thermal resistance

Approvals	RoHS-2 Compliant (2015/863/EU):	Yes
Typical Properties	Colour:	White
	Density @ 20°C (g/ml):	3.1
	Thickness (mm)	0.5 – 1.0
	Hardness (Shore C)	40
	Tensile Strength (MPa):	0.15
	Thermal Conductivity:	5.0 W/m.K
	Temperature Range:	-50°C to +150°C
	Thermal Resistance (°C.in ² /W):	0.70
	Elongation (%):	60
	Volume Resistivity (Ω·cm):	1.0 x 10 ¹⁰
	Dielectric Strength (kV/mm):	7.0
	Dielectric Constant @1MHz:	5.0
	Dielectric Loss:	0.01
	Compression Ratio (% @ 50psi):	25
	Weight Loss (120°C, 7 days):	2.0%

<u>Description</u>	<u>Order Code</u>	<u>Dimension of Gap Pad</u>
<u>Gap Pad</u>	GP500S	200 x 200 x 0.5 mm
<u>Gap Pad</u>	GP500SL	200 x 200 x 1.0 mm

Revision 2: October 2017

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,
 Ashby de la Zouch,
 Leicestershire LE65 1JR
 T +44 (0)1530 419 600
 F +44 (0)1530 416 640
 BS EN ISO 9001:2008
 Certificate No. FM 32082