
Crystal Oscillator SMD 2520 (2.5mm × 2mm × 0.8mm)

multicomp

RoHS

Compliant



Application

Used in WLAN, Bluetooth, DSC, PC, Mobile phone, TV, DVC, Telecommunications, HDD, etc


Features

- · 2520 size, 0.8mm height, ultra small SMD seam sealed clock oscillator unit.
- Low voltage operation
- Frequency Range: 4MHz to 48MHz
- 3-state function
- Automatic mounting and reflow soldering

Electrical Specifications

Output Type	: CMOS
Output Load	: 15pF
Oscillation Mode	: Fundamental
Supply Voltage	: 2.5V
Frequency Range	: 4 ~ 48MHz
Frequency stability	: ±50ppm
Operating Temperature Range	: -40°C ~ +85°C
Storage Temperature Range	: -55°C ~ +125°C
Voltage Vol (Max.) / Voh (Min.)	: 0.1VDD / 0.9VDD
Rise(Tr) / Fall(Tf) Time	: 5ns Max.
Supply Current	: 10mA Max.
Symmetry	: 45 ~ 55%
Start-up Time	: 5ms Max.
Phase Jitter (12kHz ~ 20MHz)	: 1ps Max.
Aging (at 25°C)	: ±3ppm/Year Max.

Diagram



www.element14.com www.farnell.com www.newark.com



Dimensions : Millimetres

Part Number Table

Description	Part Number
Crystal Oscillator, 2520, 4MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-4.00-2.5-50-C
Crystal Oscillator, 2520, 5MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-5.00-2.5-50-C
Crystal Oscillator, 2520, 7.3728MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-7.3728-2.5-50-C
Crystal Oscillator, 2520, 12.288MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-12.288-2.5-50-C
Crystal Oscillator, 2520, 13MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-13.00-2.5-50-C
Crystal Oscillator, 2520, 14.31818MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-14.31818-2.5-50-C
Crystal Oscillator, 2520, 14.7456MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-14.7456-2.5-50-C
Crystal Oscillator, 2520, 19.2MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-19.20-2.5-50-C
Crystal Oscillator, 2520, 22.579MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-22.579-2.5-50-C
Crystal Oscillator, 2520, 24MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-24.00-2.5-50-C
Crystal Oscillator, 2520, 24.576MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-24.57600-2.5-50-C
Crystal Oscillator, 2520, 28.63636MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-28.63636-2.5-50-C
Crystal Oscillator, 2520, 36MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-36.00-2.5-50-C
Crystal Oscillator, 2520, 38.4MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-38.4-2.5-50-C
Crystal Oscillator, 2520, 40MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-40.00-2.5-50-C
Crystal Oscillator, 2520, 48MHz, 2.5V, ± 50ppm, -40 ~ +85°C, 15pF	MCSJK-2N-48.00-2.5-50-C

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com

