

## Normal Wall Tubing (3X)

Environment Friendly, Flexible, Highly Flame Retardant, Polyolefin, Heat Shrink

pro-POWER

RoHS  
Compliant



### Description

Provides both commercial and military applications electrical insulation and protects in-line components, disconnect terminals and splices with its high strength and excellent resilience. Bundles wires for very flexible light-duty harnesses. Identifies or colour-codes wires, cables, terminals and components.

### Specifications

Operating temperature	: -55°C to +135°C
Minimum Full Recovery Temperature	: 120°C
Minimum shrink temperature	: 70°C
Shrink Ratio	: 3:1
Colours	: Black and Natural
Approvals	: UL224, 125°C 600V VW-1
Resistant to common fluids and solvents	
Meets the AMS- DTL-23053/5 class1&3	

### Technical Data

Property	Test Method	Typical Data
Tensile Strength	ASTM D 2671	≥10.4MPa
Ultimate Elongation	ASTM D 2671	≥200%
Longitudinal Shrinkage	UL 224	±5%
Heat Aging Tensile Strength Ultimate Elongation	158°C, 168hrs	≥7.3MPa ≥100%
Flammability	UL224 VW-1	Pass
Heat shock (250°C, 4hrs)	ASTM D 2671	No cracking
Cold bend tests (-55°C, 4hrs)	ASTM D 2671	No cracking
Dielectric Strength	ASTM D 150	≥15kV/mm
Volume Resistivity	ASTM D 876	≥1×10 <sup>14</sup> Ω·Cm
Copper Stability	UL224	Pass
Copper Corrosion	UL224	No corrosion

## Normal Wall Tubing (3X)

Environment Friendly, Flexible, Highly Flame Retardant, Polyolefin, Heat Shrink

**pro-POWER**

Part Number	Size		As supplied	After Recovery	
	Inch	mm	Internal diameter Min.(mm)	Internal diameter Max. (mm)	Wall thickness Nom. (mm)
PP001953	1/16	1.5	1.5	0.5	0.45 ±0.1
PP001954					
PP001965					
PP001966					
PP001955	1/8	3	3	1	0.55 ±0.1
PP001956					
PP001967					
PP001968					
PP001957	1/4	6	6	2	0.65 ±0.1
PP001958					
PP001969					
PP001970					
PP001959	1/2	12	12	4	0.75 ±0.15
PP001960					
PP001971					
PP001972					
PP001961	3/4	18	18	6	0.85 ±0.15
PP001962					
PP001973					
PP001974					
PP001963	1-1/4	30	30	10	1.1 ±0.2
PP001975					
PP001964	2.36	60	60	20	2.6 ±0.2
PP001976					

### Part Number Table

Description	Part Number
Tubing, Heat Shrink, 3:1, MIL Spec, 1.5mm, Black, 25m	PP001953
Tubing, Heat Shrink, 3:1, MIL Spec, 1.5mm, Black, 5m	PP001954
Tubing, Heat Shrink, 3:1, MIL Spec, 3mm, Black, 25m	PP001955
Tubing, Heat Shrink, 3:1, MIL Spec, 3mm, Black, 5m	PP001956
Tubing, Heat Shrink, 3:1, MIL Spec, 6mm, Black, 25m	PP001957
Tubing, Heat Shrink, 3:1, MIL Spec, 6mm, Black, 5m	PP001958
Tubing, Heat Shrink, 3:1, MIL Spec, 12mm, Black, 25m	PP001959
Tubing, Heat Shrink, 3:1, MIL Spec, 12mm, Black, 5m	PP001960

www.element14.com  
 www.farnell.com  
 www.newark.com  
 www.cpc.co.uk

**pro-POWER**

## Normal Wall Tubing (3X)

Environment Friendly, Flexible, Highly Flame Retardant, Polyolefin, Heat Shrink

pro-POWER

Description	Part Number
Tubing, Heat Shrink, 3:1, MIL Spec, 18mm, Black, 25m	PP001961
Tubing, Heat Shrink, 3:1, MIL Spec, 18mm, Black, 5m	PP001962
Tubing, Heat Shrink, 3:1, MIL Spec, 30mm, Black, 5m	PP001963
Tubing, Heat Shrink, 3:1, MIL Spec, 60mm, Black, 5m	PP001964
Tubing, Heat Shrink, 3:1, MIL Spec, 1.5mm, Natural, 25m	PP001965
Tubing, Heat Shrink, 3:1, MIL Spec, 1.5mm, Natural, 5m	PP001966
Tubing, Heat Shrink, 3:1, MIL Spec, 3mm, Natural, 25m	PP001967
Tubing, Heat Shrink, 3:1, MIL Spec, 3mm, Natural, 5m	PP001968
Tubing, Heat Shrink, 3:1, MIL Spec, 6mm, Natural, 25m	PP001969
Tubing, Heat Shrink, 3:1, MIL Spec, 6mm, Natural, 5m	PP001970
Tubing, Heat Shrink, 3:1, MIL Spec, 12mm, Natural, 25m	PP001971
Tubing, Heat Shrink, 3:1, MIL Spec, 12mm, Natural, 5m	PP001972
Tubing, Heat Shrink, 3:1, MIL Spec, 18mm, Natural, 25m	PP001973
Tubing, Heat Shrink, 3:1, MIL Spec, 18mm, Natural, 5m	PP001974
Tubing, Heat Shrink, 3:1, MIL Spec, 30mm, Natural, 5m	PP001975
Tubing, Heat Shrink, 3:1, MIL Spec, 60mm, Natural, 5m	PP001976

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)  
[www.cpc.co.uk](http://www.cpc.co.uk)

pro-POWER