

# DC Power Supply



## Features

- Triple Output
- Constant Voltage & Constant Current Functions
- Series or Parallel Operation
- Master-Slave Tracking
- Current Limitation
- Auto Switching between Voltage & Current

[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)  
[www.cpc.co.uk](http://www.cpc.co.uk)



# DC Power Supply



## Specifications

Parameters		Range
Output Voltage	CH1, CH2	0 to 32V
	CH3	5V
Output Current	CH1, CH2	0 to 3A
	CH3	2A
Overload Effect		CV: $\leq 1 \times 10^{-4} + 2\text{mV}$ , CC: $\leq 20\text{mA}$
Ripple & Noise		CV: $\leq 1\text{m Vrms}$ , CC: $\leq 1\text{m Arms}$
Regulation		CV: 20mV (Typical), CC: 50mA (Typical)
Mutual Effect		CV: $5 \times 10^{-5} + 1\text{mV}$ , CC: $< 0.5\text{mA}$
Tracking Error		$5 \times 10^{-3} + 2\text{mV}$
Reliability		MTBF (e): $\geq 2000$ hours
Indication Method		3 Digital LED Display

## General Characteristics

Input Voltage	: 110VAC / 47Hz to 63Hz
Power Cord	: US Power Cord with 3 Pins (B Type Plug, 125V/10A)
Colour	: White & Grey
Weight	: 4kg
Size (W × H × D)	: 305mm × 152mm × 210mm

## Accessories

Power Cord and Instruction Manual.

## Part Number Table

Description	Part Number
DC Power Supply, Adjustable, 3-Channel, 32V, 3A, US	72-8695A

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)  
[www.cpc.co.uk](http://www.cpc.co.uk)

