

TECHNICAL DATA SHEET

PRO-ELEC

2 Gang 16A 110V Open Drum Cable Reel with 25M Cable PL15886

**RoHS
Compliant**

Specification	
Description	Material
Socket base and cover	FRPP Black
Socket outlets	EN60309 socket, Model HP-413-4, yellow
Cable reel case	PP, Yellow reel
Metal stand	Steel, Black
Thermal cutout	56°±5°C
Cover Screw	Mild steel nickel plated
Plug	EN60309 plug, Model HP-213-4, yellow
Cable	PVC, H05VV-F 3G1.5mm ² , Yellow

Voltage	Current Rating	Cable Reel	Socket
110V AC Maximum current: Fully wound: Maximum current: Fully unwound:	16A 7 Amp (770 Watts) 16Amp (1760 Watts)	BS EN 61242	EN60309

Conditions of use

1. Ambient temperature in the range -5° C to +40° C, the average value over 24 hours not exceeding 25° C.
2. Situation not subject to exposure to direct radiation from the sun or other source of heat like to raise temperatures above the limits specified in 1.
3. Altitude not exceeding 2000 metres above sea level;
4. Atmosphere not subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions.



Important Notice : This data sheet and its contents (the "Information") belong to pro-ELEC. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-ELEC assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-ELEC was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-ELEC's liability for death or personal injury resulting from its negligence.

PRO-ELEC