

Productname : Rust Converter Creationdate : 29.06.17 Version : 4.0
 Ref.Nr.: BDS000397_3_20170629 (EN) Replaces: BDS000397_20160912

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rust Converter
Bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba
 Touwslagerstraat 1
 9240 Zele
 Belgium
 Tel.: +32(0)52/45.60.11
 Fax.: +32(0)52/45.00.34
 E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Not classified
 Classification is based on test data.
Health: Reproductive toxicity, category 1B
 May damage fertility or the unborn child .



Productname :	Rust Converter	Creationdate :	29.06.17 Version : 4.0
Ref.Nr.:	BDS000397_3_20170629 (EN)	Replaces:	BDS000397_20160912

Skin sensitization, category 1
 May cause an allergic skin reaction.
 Eye irritation, category 2
 Causes serious eye irritation.

Classification based on calculation method.

Environment: Hazardous to the aquatic environment, chronic category 3
 Harmful to aquatic life with long lasting effects.

Classification based on calculation method.

Other hazards : Restricted to professional users.

Other hazards : Not classified

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:
 2-Hydroxy-5-nonyl(branched)-benzaldehyde oxime

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s): H360 : May damage fertility or the unborn child .
 H317 : May cause an allergic skin reaction.
 H319 : Causes serious eye irritation.
 H412 : Harmful to aquatic life with long lasting effects.
P201 : Obtain special instructions before use.
P202 : Do not handle until all safety precautions have been read and understood.
P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 : Contaminated work clothing should not be allowed out of the workplace.
P308/313 : IF exposed or concerned: Get medical advice/attention.
P333/313 : If skin irritation or rash occurs: Get medical advice/attention.
P337/313 : If eye irritation persists: Get medical advice/attention.
P405 : Store locked up.
P501-2 : Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard information: Restricted to professional users.

Dir. 2004/42/EC on the limitation of emissions of volatile organic compounds (VOC) of organic solvents in certain paints and varnishes and vehicle refinishing products Cat. IIA (i) VOC max 140 g /L

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.



CRC Industries Europe bvba

Touwslagerstraat 1, 9240 Zele – Belgium

Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

2 / 10

Productname : Rust Converter **Creationdate :** 29.06.17 Version : 4.0
Ref.Nr.: BDS000397_3_20170629 (EN) **Replaces:** BDS000397_20160912

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	01-211947108-36	111-76-2	203-905-0	2.5-10	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, Skin Irrit. 2	H332,H312,H302,H319,H315	A
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	01-2119475104-44	112-34-5	203-961-6	<2.5	Eye Irrit. 2	H319	A
zinc oxide	01-2119463881-32	1314-13-2	215-222-5	<2.5	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	B
2-Hydroxy-5-nonyl(branched)-benzaldehyde oxime	01-2119486798-12	174333-80-3	605-717-8	1-2.5	Repr. 1B, Skin Sens. 1, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 1	H360,H317,H315,H318,H410	
Explanation notes							
A : substance with Community workplace exposure limit							
B : substance with national established workplace exposure limit							

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	If substance has got into eyes, immediately wash out with water for at least 15 minutes Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice
Contact with skin :	Take off immediately all contaminated clothing. Wash with water and soap. Seek medical advice
Inhalation :	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
Ingestion :	If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness Symptoms : sore throat, cough
Ingestion :	May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause sensitization by skin contact. Irritating to skin Symptoms : redness and pain
Eye contact :	Irritating to eyes Symptoms : redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment needed



Productname : Rust Converter
Ref.Nr.: BDS000397_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS000397_20160912

General Advice : If you feel unwell, seek medical advice (show the label where possible)
If symptoms persist always call a doctor
May cause adverse reproductive effects

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

May give off noxious and toxic fumes in a fire

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes
Wear breathing apparatus

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.
Ensure adequate ventilation
Wear suitable protective clothing including eye/face protection.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.



Productname : Rust Converter
Ref.Nr.: BDS000397_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS000397_20160912

Wash thoroughly after use
 Wear protective gloves/protective clothing/eye protection/face protection.
 Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.
 Keep out of reach of children.

7.3. Specific end use(s)

Anti Corrosion Products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	111-76-2	TWA	20 ppm
		STEL	50 ppm
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	112-34-5	TWA	10 ppm
		STEL	15 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices.
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type A)
hands and skin :	When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	Nitrile
eyes :	Wear safety eyewear according to EN 166.

SECTION 9: Physical and chemical properties



Productname : Rust Converter
Ref.Nr.: BDS000397_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS000397_20160912

9.1. Information on basic physical and chemical properties

Apperance : physical state : Viscous liquid.
colour : Blue-green.
odour : Odorless.
pH : 2.5-3.5
Boiling point/range : Not available.
Flash point : None
Evaporation rate : Not applicable.
Explosion limits : upper limit : Not available.
lower limit : Not available.
Vapour pressure : Not available.
Relative density : 1.2 g/cm³ (@ 20°C).
Solubility in water : Soluble in water
Auto-ignition : > 200 °C

9.2. Other information

VOC = volatile organic compounds 73 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

In case of fire, do not breathe fumes
May give off noxious and toxic fumes in a fire

10.4. Conditions to avoid

heat

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂



Productname : Rust Converter Creationdate : 29.06.17 Version : 4.0
 Ref.Nr.: BDS000397_3_20170629 (EN) Replaces: BDS000397_20160912

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met
skin corrosion/irritation: based on available data the classification criteria are not met
serious eye damage/irritation: Causes serious eye irritation.
respiratory or skin sensitisation: May cause an allergic skin reaction.
germ cell mutagenicity: based on available data the classification criteria are not met
carcinogenicity: based on available data the classification criteria are not met
toxicity for reproduction: May damage fertility or the unborn child .
STOT-single exposure: based on available data the classification criteria are not met
STOT repeated exposure: based on available data the classification criteria are not met
aspiration hazard: based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion : May cause gastrointestinal disturbances
Skin contact : May cause sensitization by skin contact.
Eye contact : Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
zinc oxide	1314-13-2	LC50 inhal.rat	> 5.7 mg/l

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3
 Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
zinc oxide	1314-13-2	IC50 algae	0.136 mg/l
		LC50 fish	0.169 mg/l
		EC50 daphnia	1.7 mg/l

12.2. Persistence and degradability

No experimental data available



Productname : Rust Converter
Ref.Nr.: BDS000397_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS000397_20160912

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Soluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.
Do not discharge into drains or the environment, dispose to an authorised waste collection point.
Contaminated packaging : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : Not classified as hazardous for transport

14.2. UN proper shipping name

Proper shipping name: Not applicable.

14.3. Transport hazard class(es)

Class: Not applicable.
ADR/RID - Classification code: Not applicable.

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally No



Productname : Rust Converter
Ref.Nr.: BDS000397_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS000397_20160912

hazardous:

IMDG - Marine pollutant: No

IATA/ICAO - Environmentally hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: Not applicable.

IMDG - Ems: Not applicable.

IATA/ICAO - PAX: Not applicable.

IATA/ICAO - CAO: Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H360 : May damage fertility or the unborn child .
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : 8.2. Exposure controls
acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.



Productname :	Rust Converter	Creationdate :	29.06.17 Version : 4.0
Ref.Nr.:	BDS000397_3_20170629 (EN)	Replaces:	BDS000397_20160912

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

