

AC Open-Jaw Clamp Meter



RoHS
Compliant



Features

- Compact Size
- 4000 Counts LCD Display with Backlight
- 200A AC Current
- Non-contact Voltage
- Data Hold
- REL Mode
- Auto Power Off
- Low Battery Indication
- 1.2" (30mm) Jaw Opening

Specifications

Function	Range	Accuracy (% of reading + digits)	Resolution
DC Voltage	4V	$\pm(1.5\% + 2d)$	1mV
	40V	$\pm(1.5\% + 2d)$	10mV
	400V	$\pm(1.5\% + 2d)$	100mV
	600V	$\pm(2\% + 2d)$	1V

Input Impedance : 10M Ω

Over rang protection : 600V DC or 600V AC rms

Function	Range	Accuracy (% of reading + digits)	Resolution
AC Voltage	4V	$\pm(2\% + 5d)$	1mV
	40V	$\pm(1.5\% + 2d)$	10mV
	400V	$\pm(1.5\% + 2d)$	100mV
	600V	$\pm(2\% + 2d)$	1V

Input Impedance : 10M Ω

Over rang protection : 600V DC or 600V AC rms

Frequency Response : 50Hz ~ 400Hz

Function	Range	Accuracy (% of reading + digits)	Resolution
AC Current	200A	$\pm(3\% + 5d)$	100mA

Over rang protection : Maximum input 200A

Frequency Response : 50Hz~60Hz

Function	Range	Accuracy (% of reading + digits)	Resolution
Resistance	400 Ω	$\pm(1.0\% + 4d)$	0.1 Ω
	4k Ω	$\pm(1.5\% + 4d)$	1 Ω
	40k Ω	$\pm(1.5\% + 4d)$	10 Ω
	400k Ω	$\pm(1.5\% + 4d)$	100 Ω
	4M Ω	$\pm(2.5\% + 4d)$	1k Ω
	40M Ω	$\pm(3.5\% + 4d)$	10k Ω



AC Open-Jaw Clamp Meter



Over rang protection : 250V DC or 250V AC rms

Function	Range	Accuracy (% of reading + digits)	Resolution
Frequency	40Hz	$\pm(1.0\% + 2d)$	0.01Hz
	400Hz	$\pm(1.2\% + 2d)$	0.1Hz
	4KHz	$\pm(1.2\% + 2d)$	1Hz
	40KHz	$\pm(1.2\% + 2d)$	10Hz
	400KHz	$\pm(1.2\% + 2d)$	100Hz
	10MHz	$\pm(1.2\% + 2d)$	100Hz

Input sensitivity : 10mV rms

Over rang protection : 300V DC or 300V AC rms

Function	Range	Accuracy (% of reading + digits)	Resolution
Duty Cycle	0.1%~99.9%	$\pm 1.2\%$ of rdg ± 2 dgts	0.1%

Sensitivity : <0.5V rms

Pulse width : >100 μ s, <100ms

Overload protection : 300V DC or 300V AC rms

Function	Range	Accuracy (% of reading + digits)	Resolution
Temperature	-20°C to 760°C	$\pm(3.0\% \pm 5^\circ\text{C})$	0.1°C
	4°F to 1400°F	$\pm(3\% \pm 8^\circ\text{F})$	1°F

Sensor : K Type banana Play

Over rang protection : 250V DC or 250V AC rms

Function	Range	Accuracy (% of reading + digits)	Resolution
Capacitance	4nF	$\pm(5\% + 20d)$	0.1nF
	40nF	$\pm(3.0\% + 5d)$	1nF
	400nF	$\pm(3.0\% + 5d)$	10nF
	4 μ F	$\pm(3.0\% + 5d)$	100nF
	40 μ F	$\pm(3.0\% + 5d)$	1 μ F
	100 μ F	$\pm(5.0\% + 10d)$	10 μ F

Over range protection : 250V DC or 250V AC rms

Capacitance	Over rang protection: 250V DC or 250V AC rms
	Over rang protection: 250V DC or 250V AC rms

Part Number Table

Description	Part Number
AC Open-Jaw Clamp meter, 200A, 30mm Jaw	72-14440

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

