

# Sealed Sub-Miniature Toggle Switch **multicomp**

RoHS  
Compliant



## Specifications

Contact Configuration	: SPDT, On-None-On
Actuator	: 6.10mm Height
Bushing	: SP, 4.65mm Height
Termination	: Vertical, Through Hole, PC Mount
Contact Rating	: 0.4VA Max. @20V Max. (AC or DC)
Mechanical Life	: 30,000 make-and-break cycles
Contact Resistance	: 20mΩ max. Initial @ 2-4VDC
Contact Current	: 100mA for Gold Plated Contacts
Insulation Resistance	: 1,000MΩ min.
Dielectric Strength	: 1,000Vrms min. @ sea level
Operating Temperature	: -40°C to 85°C

## Material Specifications

Case & Bushing	: Glass Filled Nylon 6.6, Flame Retardant, Heat Stabilized
Actuator	: Brass, Chrome Plated, Internal O-ring seal
Switch Support	: Brass, Tin Plated
Contact / Terminal	: Copper Alloy, Gold Plated
Seal	: Standard Epoxy

## Soldering Process

Manual Soldering	: Use soldering iron of 30 watts, controlled at 350°C approx. 5sec while applying solder.
Wave Soldering	: Recommended soldering Temperature: 270 ±5°C Duration of soldering immersion: Max. 5 sec. (PCB is 1.6mm in thickness)


## Switch Function

No. Poles	Switch Function		
	Pos.1	Pos.2	Pos.3
SP	ON	NONE	ON

# Sealed Sub-Miniature Toggle Switch


## Actuator Option

T2




## Bushing Option

A1



## Termination Option

M2



Dimensions : Inches (Millimetres)

## Part Number Table

Description	Part Number
Sealed Sub-Miniature Toggle Switch, Non-Illuminated, SPDT, On-None-On, Vertical, PCB	MC2AS1T2A1M2RE

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com  
www.farnell.com  
www.newark.com

