

# Straight 3P XLR MIC Plug

pro-SIGNAL




## Specifications

Gender	: Plug
No. of Poles	: 3P
Mounting Type	: Cable
External Diameter	: 18.8mm
Cable Diameter	: 4mm ~ 7.2mm Cable
Boot Colour	: Black
Cap Colour	: Black

## Electrical Specifications

Current Rating	: 3P/15A
Withstand Voltage	: 1,500V AC
Contact Resistance	: 3mΩ Max.
Insulator Resistance	: 5000MΩ Min.

## Diagram



Dimensions : Millimetres

## Material Specifications

No.	Description	Material	Plating
1	Die-Cast Shell	Zinc Alloy (ZZnAL4-0)	Electro-Coating Black
2	Pin	Brass (H59-1)	Silver
3	Insulator	PA	Black
4	Terminal	Brass (H62)	Tin
5	Chuck	POM	White
6	CAP	PA	Black
7	T-Ring	POM	White
8	Boot	PVC	Black

## Part Number Table

Description	Part Number
Straight 3P XLR MIC Plug, Cable, Zinc Alloy/ Electro-Coating Black	PS000228

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell Limited 2016.