ZB5FV063

flush mounted blue pilot light head for integral led

Product availability : Stock - Normally stocked in distribution facility





Main

4-1-		
Vain Rener of another		
Range of product	Harmony XB5	
Product or component type	Head for pilot light	
Product compatibility	Integral LED	
Device short name	ZB5	
Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Head type	Built-in-flush	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Cap/Operator or lens colour	Blue	
Operator additional information	With plain lens	
Complementary CAD overall width	1.46 in (37 mm)	
CAD overall height	1.46 in (37 mm)	
CAD overall depth	1.18 in (30 mm)	
Product weight	0.03 lb(US) (0.015 kg)	
Electrical composition code	P1 in front mounting with integral LED P2 in front mounting with integral LED and transformer PF1 in front mounting with integral LED	
Environment		
Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II IEC 60536	
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529	
Con 10, 2010		

Complementary

CAD overall width	1.46 in (37 mm)	
CAD overall height	1.46 in (37 mm)	
CAD overall depth	1.18 in (30 mm)	
Product weight	0.03 lb(US) (0.015 kg)	
Electrical composition code	P1 in front mounting with integral LED P2 in front mounting with integral LED and transformer PF1 in front mounting with integral LED	

Environment

Protective treatment	TH	2
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II IEC 60536	C
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529	

	IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m
IK degree of protection	IK03 conforming to IEC 50102
Standards	CSA C22.2 No 14 EN/IEC 60947-5-5 UL 508 JIS C 4520 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-1
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27

Ordering and shipping details

Category	22467 - PUSHBUTTONS,22MM(PLASTIC) NEW
Discount Schedule	CS2
GTIN	00785901054054
Nbr. of units in pkg.	1
Package weight(Lbs)	5.0000000000003E-2
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov