
UL 1571 Stranded Hook-up Wire

pro-**Power**

RoHS

Compliant



Specifications

Conductor Material Insulator Material Rated Temperature Rated Voltage Cable Length : Stranded Tinned Copper


: PVC

: 80°C

: 300V

: Available in 305m Reel or in per metre length

Diagram



Diamet	
1975	
15	Length
Q	1 -

AWG	Construction # Strands/Strand Size (mm)	Conductor Dia. (mm)	Insulation Diameter (mm)	Conductor Resistance 20°C (Ω/kM)	Insulation Colour	Part Number
26 7/0.16		0.40		104 74	Black	PP002417
					Blue	PP002418
					Brown	PP002419
	7/0.16				Green	PP002420
	0.49	1	124.71	Red	PP002421	
				Purple	PP002422	
					White	PP002423
					Yellow	PP002424
28 7/0.127					Black	PP002425
					Blue	PP002426
				Brown	PP002427	
	7/0 407	0.39	0.9	197.94	Grey	PP002428
	//0.127				Red	PP002429
					Purple	PP002430
					White	PP002431
					Yellow	PP002432
30	7/0.10	0.31	0.8	319.26	Black	PP002433
					Blue	PP002434

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



AWG	Construction # Strands/Strand Size (mm)	Conductor Dia. (mm)	Insulation Diameter (mm)	Conductor Resistance 20°C (Ω/kM)	Insulation Colour	Part Number
30 7/0.10	0.31	0.8	319.26	Brown	PP002435	
				Green	PP002436	
				Red	PP002437	
				White	PP002438	
				Yellow	PP002439	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

