

Laser Distance Meter

TENMA™

RoHS
Compliant



Features

- Continuous Measurement
- Measures Distance / Area / Volume
- Display Units: Inches, feet and meters
- Auto Power / Laser Off : 150s
- Audio Alarm

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

TENMA™

Laser Distance Meter



Electrical Specifications

Parameter	Range
Distance	0.05 ~ 35m $\pm(1.5\text{mm}+d \times 5/100000)$
Min. Unit	1mm
Max. Laser Power	< 1mW
Laser Wave Length	635nm
Battery life	8000 times of measurement
Operating Temperature	0° C ~ 40° C
Storage Temperature	-20° C ~ 60° C
Storage Humidity	20% ~ 80% RH

General Characteristics

Battery	: 1.5V AAA Alkaline Battery × 2
Colour	: Orange and Grey
Weight	: 84g
Dimension	: 112mm × 50mm × 25 mm

Accessories

AAA Battery, Hanging Cord, Carrying Bag and Instruction Manual

Part Number Table

Description	Part Number
Laser Distance Meter, 35m	72-13560

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

