

**160 iSS VDE Insulated screwdriver with reduced blade diameter for slotted screws,
0,8 x 4,0 x 100 mm
Kraftform Plus – Series 100 VDE**



| | | | |
|------------------------|---------------|-------------------------------|--------------|
| EAN: | 4013288179548 | Size: | 161x26x26 mm |
| Part number: | 05020129001 | Weight: | 35 g |
| Article number: | 160 iSS | Country of origin: | CZ |
| | | Customs tariff number: | 82054000 |

- Insulated VDE blades for secure work at 1,000 volts
- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Take it easy tool finder: colour coding according to profile and size
- Hexagonal anti-roll feature against rolling away
- Reduced blade and handle diameter

VDE insulated slotted screwdriver with reduced blade and handle diameter, suitable for actuating low-lying screws in particularly confined working spaces. Multi-component Kraftform Plus handle for fast and low-fatigue working: hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. Individually tested in water bath at 10,000 volts for secure work at the permissible voltage of 1,000 volts. "Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool. The hexagonal anti-roll feature prevents any bothersome rolling away at the workplace.



Web link

http://products.wera.de/en/vde_tools_kraftform_plus_series_100_vde_160_iss.html


Wera - 160 iSS
05020129001 - 4013288179548

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

The super slim VDE screwdrivers



Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.



The super slim VDE screwdrivers for installation jobs in particularly confined spaces. Not only do the blades have a reduced diameter, the handles also have a very slim design.

Individually tested




The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Impact strength test



Impact strength tested at -40°C , guaranteeing safety even under extreme conditions.

Multicomponent Kraftform handle



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces – resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any “sticking” of the hand to the handle, making rapid repositioning of the hand possible.

Rapid hand repositioning




The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking” to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.

Prevents hand injuries



The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

“Take it easy” Toolfinder



Screwdrivers with “Take it easy” tool finder: colour coding according to profile and size stamp.

Web link

http://products.wera.de/en/vde_tools_kraftform_plus_series_100_vde_160_iss.html







Wera - 160 iSS
05020129001 - 4013288179548

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

160 iSS VDE Insulated screwdriver with reduced blade diameter for slotted screws,
 0,8 x 4,0 x 100 mm
 Kraftform Plus – Series 100 VDE



Further versions in this product family:

| |  mm |  mm |  mm |  mm |  inch |  inch |
|-------------|---|---|---|--|---|---|
| 05020129001 | 0.8 | 4.0 | 100 | 81 | 5/32 | 4 |

Web link

http://products.wera.de/en/vde_tools_kraftform_plus_series_100_vde_160_iss.html

Wera - 160 iSS

05020129001 - 4013288179548

Wera Werkzeuge GmbH

Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de