



Specification
EZ150
E-ZE Check Xtra



Nominal operating voltage: 230V
Frequency: 50Hz
Non-trip Earth loop impedance ranges:
0-1.7-5-10-100-200-500Ω
Earth loop threshold accuracy:
±(10% + 0.3Ω) *

Voltage low indication: <195V ± 5%
Voltage high indication: >270V ± 5%
Earth neutral voltage high indication: > 30V ± 5%
Open earth indication: >500Ω
Temperature Range: -10 to 40°C, non-condensing.
Dimensions: Approx 65mm x 65mm x 50mm **Weight:** Approx 64g
Power supply: From mains
Power consumption: <2.5W
Overvoltage category: Cat II / 300V
Pollution degree: 2
Safety: Complies with BS EN 61010-1:1993

* **Note:** Measurement accuracy can be affected by highly inductive or capacitive loads distributed on the supply (see section 3.3.4)

14



Specification
EZ650
E-ZE Check Xtra Pro



EZ650 E-Ze Check Xtra Pro is supplied with an IEC socket with an interchangeable 3 pin adaptor and a 3 way flying lead with croc clips allowing testing at light fittings, junction boxes and terminals.

Nominal operating voltage: 230V
Frequency: 50 Hz

Non-trip Earth loop impedance ranges: 0-1.7-5-10-100-200-500Ω
Earth loop threshold accuracy: ±(10% + 0.3Ω) *
Voltage low indication: <195V ± 5%
Voltage high indication: >270V ± 5%
Earth neutral voltage high indication: >30V ± 5%
Open earth indication: >500Ω
Temperature Range: -10 to 40°C, non-condensing
Dimensions: 315mm x 260mm x 85mm **Weight:** Approx 1kg
Power supply: From mains
Power consumption: <2.5W
Overvoltage category: Cat II / 300V
Pollution degree: 2

Safety: Complies with BS EN 61010-1:1993

* **Note:** Measurement accuracy can be affected by highly inductive or capacitive loads distributed on the supply (see section 3.3.4)



Specification
EZ650/C/13A
E-ZE Check Xtra



EZ650/C/13A E-Ze Check Xtra is supplied with an IEC socket with an interchangeable 3 pin adaptor and a 13A plug lead.

Nominal operating voltage: 230V
Frequency: 50 Hz

Non-trip Earth loop impedance ranges: 0-1.7-5-10-100-200-500Ω
Earth loop threshold accuracy: ±(10% + 0.3Ω) *
Voltage low indication: <195V ± 5%
Voltage high indication: >270V ± 5%
Earth neutral voltage high indication: >30V ± 5%
Open earth indication: >500Ω
Temperature Range: -10 to 40°C, non-condensing
Dimensions: 315mm x 260mm x 85mm **Weight:** Approx 1kg
Power supply: From mains
Power consumption: <2.5W
Overvoltage category: Cat II / 300V
Pollution degree: 2
Safety: Complies with BS EN 61010-1:1993

* **Note:** Measurement accuracy can be affected by highly inductive or capacitive loads distributed on the supply (see section 3.3.4)

Check out what else you can get from Martindale:

- 18th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers



Martindale Electric Company Limited
Metrohm House, Imperial Park, Imperial Way, Watford, WD24 4PP, UK
Tel: +44(0)1923 441717 Fax: +44 (0)1923 446900
E-mail: sales@martindale-electric.co.uk
Website: www.martindale-electric.co.uk



© Martindale Electric Company Ltd. 2018
Registered in England No. 3387451. Rev 3 LITEZ650