

# Straight 4mm Banana Plug to Plug Safety Patchcord - 2.5mm<sup>2</sup> PVC



## Specifications

Lead Length	: 500mm/19.7" 1m / 3.3ft 2m / 6.6ft
Connector Type A	: Straight 4mm Shrouded Banana Plug
Connector Type B	: Straight 4mm Shrouded Banana Plug
Voltage Rating	: CAT IV 1000V
Current Rating	: 36A
Resistance	: 500mm: 15mΩ 1m: 20mΩ 2m: 30mΩ
Cable	: 2.5mm <sup>2</sup> , PVC
Contact Material	: Brass and Beryllium Copper, Nickel Plated
Insulator Material	: Polypropylene
Insulator Colour	: White, Blue, Brown, Grey, Yellow, Yellow/Green, Black, Red and Green
Temperature	: -20°C to +80°C

## Application

General purpose electric and electronic testing, controlling and measuring.

## Part Number Table

Description	Insulator Colour	Lead Length	Part Number
Test Lead, Straight 4mm Shrouded Banana Plug to Plug, 2.5mm <sup>2</sup> PVC, 1000V, 36A	White	500mm	72-14024
	Blue		72-14026
	Yellow		72-14028
	Black		72-14030
	Red		72-14032
	Green		72-14034
	White	1m	72-13992
	Blue		72-13994
	Brown		72-13996



# Straight 4mm Banana Plug to Plug Safety Patchcord - 2.5mm<sup>2</sup> PVC



Description	Insulator Colour	Lead Length	Part Number
Test Lead, Straight 4mm Shrouded Banana Plug to Plug, 2.5mm <sup>2</sup> PVC, 1000V, 36A	Grey	1m	72-13998
	Yellow		72-14000
	Yellow/Green		72-14002
	Black		72-14004
	Red		72-14006
	Blue	2m	72-14008
	Brown		72-14010
	Grey		72-14012
	Yellow		72-14014
	Yellow/Green		72-14016
	Black		72-14018
	Red		72-14020
	Green		72-14022

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

