



## **Specifications**

Lead Length	: 1m / 3.3ft
Connector Type A	: 4mm Banana Tip Probe
Connector Type B	: Straight 4mm Shrouded Banana Plug (or) Right Angle 4mm Shrouded Banana Plug
Voltage Rating	: CAT II 1000V
Current Rating	: 20A
Cable	: 1mm², PVC
Contact Material	: Brass and Beryllium Copper, Nickel Plated
Insulator Material	: Polypropylene / Polyamide
Insulator Colour	: Red & Black
Temperature	: -20°C to 80°C

## Applications

General purpose electric and electronic testing, controlling and measuring.

## **Part Number Table**

Description	Part Number
Test Lead Kit, (One Red + One Black) 4mm Banana Tip Probe to Straight 4mm Banana Plug Safety Patchcord, PVC 1mm <sup>2</sup> , 1000V, 20A, 1m	72-14280
Test Lead Kit, (One Red + One Black) 4mm Banana Tip Probe to Right Angle 4mm Banana Plug Safety Patchcord, PVC 1mm <sup>2</sup> , 1000V, 20A, 1m	72-14282

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

