

# Stacking 4mm Banana Plug to Plug Safety Patchcord - 2.5mm<sup>2</sup> PVC



## Specifications

Lead Length	: 500mm/19.7" 1m / 3.3ft
Connector Type A	: Stacking 4mm Shrouded Banana Plug
Connector Type B	: Stacking 4mm Shrouded Banana Plug
Voltage Rating	: CAT II 1000V
Current Rating	: 36A
Resistance	: 500mm: 15mΩ 1m: 20mΩ
Cable	: 2.5mm <sup>2</sup> , PVC
Contact Material	: Brass and Beryllium Copper, Nickel Plated
Insulator Material	: Polypropylene
Insulator Colour	: White, Blue, Brown, Grey, Yellow, Black, Red, Green, Yellow/Green and Purple
Temperature	: -20°C to 80°C

## Applications

General purpose electric and electronic testing, controlling and measuring.

## Part Number Table

Description	Insulator Colour	Lead Length	Part Number
Test Lead, Stacking 4mm Shrouded Banana Plug to Plug, 2.5mm <sup>2</sup> PVC, 1000V, 36A	White	500mm	72-14096
	Blue		72-14098
	Brown		72-14100
	Grey		72-14102
	Yellow		72-14104
	Black		72-14106
	Red		72-14108
	Green		72-14112
	Blue		1m
	Brown	72-14080	



# Stacking 4mm Banana Plug to Plug Safety Patchcord - 2.5mm<sup>2</sup> PVC



Description	Insulator Colour	Lead Length	Part Number
Test Lead, Stacking 4mm Shrouded Banana Plug to Plug, 2.5mm <sup>2</sup> PVC, 1000V, 36A	Grey	1m	72-14082
	Yellow		72-14084
	Yellow/Green		72-14086
	Black		72-14088
	Red		72-14090
	Green		72-14092
	Purple		72-14094

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

