UL1571 Style Stranded Hook-Up Wire







RoHS Compliant

This stranded Hook-Up Wire meets the specifications of UL AWM/Style 1571 - 80°C / 300V. UL recognized (UL file no. E352035).


Specifications

Conductor Material : Stranded Tinned Copper

Insulator Material : PVC
Rated Temperature : 80°C
Rated Voltage : 300V

Cable Length : Available in 305m Reel or in per metre length

Diagram



Marking



AWG	Construction # Strands/Strand Size (mm)	Conductor Diameter (mm)	Insulation Diameter (mm)	Conductor Resistance 20°C (Ω/kM)	Insulation Colour	Part Number
26	7/0.16	0.49	1	124.71	Black	PP002417
					Blue	PP002418
					Brown	PP002419
					Green	PP002420
					Red	PP002421
					Purple	PP002422
					White	PP002423
					Yellow	PP002424
28	7/0.127	0.39	0.9	197.94	Black	PP002425
					Blue	PP002426
					Brown	PP002427
					Grey	PP002428

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



UL1571 Style Stranded Hook-Up Wire



AWG	Construction # Strands/Strand Size (mm)	Conductor Diameter (mm)	Insulation Diameter (mm)	Conductor Resistance 20°C (Ω/kM)	Insulation Colour	Part Number
28	7/0.127	0.39	0.9	197.94	Red	PP002429
					Purple	PP002430
					White	PP002431
					Yellow	PP002432
30	7/0.10	0.31	0.8	319.26	Black	PP002433
					Blue	PP002434
30	7/0.10	0.31	0.8	319.26	Brown	PP002435
					Green	PP002436
					Red	PP002437
					White	PP002438
					Yellow	PP002439

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

