DisplayPort Plug to HDMI Receptacle Adaptor

pro-**signal**

PIN OUT



Specifications

Convert From : DisplayPort Plug, 20 Pin Convert To : HDMI Receptacle, 19 Pin

Cable Length : 190mm Colour : Black, White

RoHS **Compliant**


Electronic Tests

Open / Short / Intermittence : 100%

Hi-Pot : AC 300V, 0.01S, 1mA Insulation Resistance : DC 300V, 0.01S, 10MΩ Min.

Conductive Resistance : 3Ω Max. Computer Test : 1080P @ 60Hz

Diagram



No.	Parameter	Specifications
1	Cable	DP 1.2 [32AWG(7/0.08TC) * 1P + D(7/0.08TC) + FAM] * 5 + 32AWG(7/0.08TC) * 5C + D(1/0.254BC) + Al-Foil + B(80/0.12 Al-Mg), PVC Jacket, OD: 4.8±0.2mm
2	Connector - A	DisplayPort Male, 20 Pin, Nickel Plated Shell, Gold Flash Contact
3	Connector - B	HDMI Female, 19 Pin, Nickel Plated Shell, Gold Flash Contact, with Chipset
4	Inner Mold	LDPE
5	Outer Mold	45P PVC
6	Hood	Mini DisplayPort Male: ABS
7	Hood	HDMI Female: ABS
8	Dust Cover	DisplayPort Male: Transparent

Part Number Table

Description	Part Number
DisplayPort Plug to HDMI Receptacle Adaptor, 190mm, Black	PS000251
DisplayPort Plug to HDMI Receptacle Adaptor, 190mm, White	PS000252

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

