



| | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------------------------|---|-----------|-------|---|--|-------------------------------|--|--|---|----------------|----------------|---------|-----------|----|-------|--|--|--------|--|--|---|--|--|
| A | 09185107322 | 3 | 4,5 |  All Dimensions in mm Original Size DIN A 4 | Techn. Character. | | | Nicht tolerierte Masse/ Free size tolerances | | | | | | | | | | | | | | | |
| | 09185106322 | 2 | 4,5 | | <table border="1"> <tr> <td></td> <td>Dat.</td> <td>Name</td> <td rowspan="4">Massstab/Scale</td> </tr> <tr> <td>Detail.</td> <td>01-FEB-00</td> <td>JB</td> </tr> <tr> <td>Insp.</td> <td></td> <td></td> </tr> <tr> <td>Stand.</td> <td></td> <td></td> </tr> </table> | | | | Dat. | Name | Massstab/Scale | Detail. | 01-FEB-00 | JB | Insp. | | | Stand. | | | SEK 18 Male connector 10 poles low profile with straight pins | | |
| | | Dat. | Name | | Massstab/Scale | | | | | | | | | | | | | | | | | | |
| | Detail. | 01-FEB-00 | JB | | | | | | | | | | | | | | | | | | | | |
| | Insp. | | | | | | | | | | | | | | | | | | | | | | |
| | Stand. | | | | | | | | | | | | | | | | | | | | | | |
| 09185105322 | 0,76 µm Au | 4,5 | 1,5:1 | | | | | | | | | | | | | | | | | | | | |
| 09185107324 | 3 | 2,9 | | | | | | | | | | | | | | | | | | | | | |
| 09185106324 | 2 | 2,9 | | | | | | | | | | | | | | | | | | | | | |
| 09185105324 | 0,76 µm Au | 2,9 | 31502 | 03-JUN-03 | JB | HARTING EURL F-95972 Paris | | | | | | | | | | | | | | | | | |
| Bestell-Nr. Part-No. Reference | Anforderungsstufe performance level Niveau de qualite | α | 29778 | 25-APR-02 | CV | | | |  | TB 0918510x32x | | | | | | | | | | | | | |
| | | | 26570 | 01-FEB-00 | JB | | | | | | | | Sub. | | | | | | | | | | |
| | | | Mod. | Dat. | Name | | | | Blatt/page 1/2 | | | | | | | | | | | | | | |