



NETTOYANT FLUX DE SOUDURE

Reference : 30680



1. General description

Blend of solvents with low surface tension, adapted for removing of all types of flux. Eliminates white traces. Fast drying.

2. Features

- Takes away chlorides and acids which could provoke corrosion and so reduce the lifetime of the pcb.
- Thanks to the integrated brush, cleaning of assembled components becomes easy.
- The brush also allows mechanical action to support the chemical cleaning.
- Penetrates quickly.
- Allows to dissolve certain protective coatings.
- Fast evaporation to minimize downtime.
- Safe on most components, indications and marks.

3. Applications

- Cleaning of all flux residues on printed circuit boards and electronic components.
- Electronic components.
- Printed circuit boards.

4. Directions

- Brush on the stubborn residues.
- Spray from a short distance.
- Repeat if necessary.
- Put the delivered brush on the nozzle of the spraycap.
- Spray liberally and allow to run off.
- Test before use on sensitive materials.
- Do not use on energized equipment.
- Allow to dry completely before reactivation.
- Protect aerosol against heat sources, welding spatters, etc...



Manufactured by :
CRC Industries Europe bvba
 Touwslagerstraat 1
 9240 Zele Belgium
 Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





NETTOYANT FLUX DE SOUDURE

Reference : 30680

- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5. Typical product data (without propellant)

	Aerosol	Bulk
Appearance	Liquid	not available
Color	colorless	colorless
Odour	solvent	solvent
Density	0.79 g/cm ³ (@ 20°C)	0.78 g/cm ³ (@ 20°C)
Dynamic viscosity	1.17 mPa.s (@ 20°C)	1.17 mPa.s (@ 20°C)
Surface tension active product	23 mN/m	not available
Kauri Butanol value active product	> 48	not available
Drying time active product	8 min	not available

6. Packaging

Aerosol	12x400 ML
Bulk	5 L

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version KF-NETT_FLUX_SOUDURE-20090612
Date 12/06/2009



Manufactured by :
CRC Industries Europe bvba
 Touwslagerstraat 1
 9240 Zele Belgium
 Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

