

Digital Clamp Meter



Features

- 3-1/2 Digits, 2000 Counts LCD Display
- Auto & Manual Ranging
- 28mm Jaw Capacity
- Diode Test and Continuity Buzzer
- Data Hold
- MAX/MIN Modes
- Low Battery Indication
- Overload Protection
- Input Impedance for DCV: 10M Ω
- 1m Drop Test

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk



Digital Clamp Meter



General Characteristics

Safety Rating	: CAT II 600V, CAT III 300V
Power	: 9V Batteries (6F22)
LCD Size	: 35.6mm × 18mm
Colour	: Orange and Grey
Weight	: 260g
Dimension	: 208mm × 76mm × 30mm
Standard Accessories	: Batteries, Test Leads & User Manual

Electrical Specifications

Parameters	Range	Best Accuracy
AC Current	20A/200A/600A	±(1.5% +5 digits)
AC Voltage	2V/20V/200V/600V	±(1.2% +5 digits)
DC Voltage	200mV/2V/20V/200V/600V	±(0.8% +1 digit)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1% +2 digits)
Jaw Capacity	28mm	

Part Number Table

Description	Part Number
Digital Clamp Meter, 28mm Jaw	72-7218

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

