eet 2H03B "#" inc	licates a packag	e specification code.		
Soldering Flow OK Welding R	OHS REACH			
	Note	es		
		Meet LF(Lead Free)[**LF : Lead content is less than 1000 ppm.], HF(Halogen Free)		
	Packaging	Specifications	Minimum quantity	
	В	Packing in bulk	500	
4.0 mm max.				
3.5 mm max.				
2.5 mm max.				
	2HO3B ** ind Soldering Soldering Welding R Soldering Soldering Soldering R 4.0 mm max. 3.5 mm max.	 ** indicates a packag Sodderfor Sodderfor<!--</th--><th>** indicates a package specification code. Solering Image: Specifications A.0 mm max. 3.5 mm max.</th>	** indicates a package specification code. Solering Image: Specifications A.0 mm max. 3.5 mm max.	

2.5 ±0.8mm

0.5 ±0.05mm

Specifications

Lead spacing F

Lead diameter d

Capacitance	10000pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	C0G(EIA)
Temperature coefficient	25 to 125°C: 0±30ppm/°C -55 to 25°C: 0+30/-72ppm/°C
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

