	muRata Capacitor Data Sheet RCER71E335K2K1H03B "#" indicates a package specification code.						
	In Production Train 2000 125 Low acoustic Defineting Crack Soldering Crack Flow OK Welding RoHS REACH						
	< List of part numbers with package codes > RCER71E335K2K1H03B						
1	Shape Notes						
			Meet LF(Lead Free)[*LF : Lead content is less than 1000 ppm.], HF(Halogen Free)				
			References				
	은 여 : 0.5±0.05		Packaging	Specifications	Minimum quantity		
			В	Packing in bulk	500		
-	Coating extension does not exceed the end of the lead bend. Lead Wire : Solder Coated Copper Wire or (in mm) Solder Coated CP Wire (in mm)						
	L size or outer diameter D (mm)	5.5 mm max.					
	Wsize	4.0 mm max.					
	T size	3.15 mm max.					
	Lead spacing F	5.0 ±0.8mm					
	Lead diameter d	0.5 ±0.05mm					

6.0mm

## Specifications

W1 size (max.)

Capacitance	3.3µF±10%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

