
KEMET Part Number: C052C151J2G5TA

(C052C151J2G5TA)



LDD Comm C0G, Ceramic, 150 pF, 5%, 200 VDC, C0G, Lead Spacing = 5.08mm



Supplier: KEMET Series: LDD Comm C0G Style: Radial Features: Commercial ROHS: With Exemptions REACH: SVHC (Pb – CAS 7439-92-1) Termination: Tin		
Style: Radial Features: Commercial ROHS: With Exemptions REACH: SVHC (Pb – CAS 7439-92-1) Termination: Tin	Supplier:	KEMET
Features: Commercial RoHS: With Exemptions REACH: SVHC (Pb – CAS 7439-92-1) Termination: Tin	Series:	LDD Comm C0G
RoHS: With Exemptions REACH: SVHC (Pb – CAS 7439-92-1) Termination: Tin	Style:	Radial
REACH: SVHC (Pb – CAS 7439-92-1) Termination: Tin	Features:	Commercial
Termination: Tin	RoHS:	With Exemptions
	REACH:	SVHC (Pb - CAS 7439-92-1)
F. 11 D. 14 N/A	Termination:	Tin
Failure Rate: N/A	Failure Rate:	N/A

General Information

Dimensions	
L	4.83mm +/-0.25mm
Н	4.83mm +/-0.25mm
Т	2.29mm +/-0.25mm
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.635mm +0.102/-0.051mm
G	1.143mm MAX

Specifications	
Capacitance:	150 pF
Capacitance Tolerance:	5%
Voltage DC:	200 VDC
Dielectric Withstanding Voltage:	500 V
Temperature Range:	-55/+125C
Temperature Coefficient:	COG
Dissipation Factor:	0.10% 1MHz 25C
Insulation Resistance:	6.667 GOhms

Packaging S	pecifications
Packaging:	Bulk, Bag
Packaging Quantity:	100

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

