
## KEMET Part Number: C052C330G2G5TA

(C052C330G2G5TA)



## LDD Comm C0G, Ceramic, 33 pF, 2%, 200 VDC, C0G, Lead Spacing = 5.08mm



Dimensions	
L	4.83mm +/-0.25mm
Н	4.83mm +/-0.25mm
Т	2.29mm +/-0.25mm
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.635mm +0.102/-0.051mm
G	1.143mm MAX

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	100	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and		
we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the		
requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us		
with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.		



© 2006 - 2019 KEMET

Style:	Radial	
Features:	Commercial	
RoHS:	With Exemptions	
REACH:	SVHC (Pb – CAS 7439-92-1)	
Termination:	Tin	
Failure Rate:	N/A	
Specifications		
Capacitance:	33 pF	
Canacitance Tolerance:	2%	

**General Information** 

KEMET

LDD Comm C0G

Supplier:

Series:

Specifications	
Capacitance:	33 pF
Capacitance Tolerance:	2%
Voltage DC:	200 VDC
Dielectric Withstanding Voltage:	500 V
Temperature Range:	-55/+125C
Temperature Coefficient:	COG
Dissipation Factor:	0.10% 1MHz 25C
Insulation Resistance:	30.303 GOhms