
KEMET Part Number: C322C751JDG5TA



GoldMax 300 Comm COG HV, Ceramic, 750 pF, 5%, 1000 VDC, COG, GoldMax, Commercial Standard, Lead Spacing = 5.08mm



Supplier: KEMET Series: GoldMax 300 Comm C0G H Style: Radial Description: GoldMax, Commercial Stan RoHS: Yes	٦V
Style: Radial Description: GoldMax, Commercial Stan	ΗV
Description: GoldMax, Commercial Stan	
,	
RoHS: Yes	dard
Termination: Tin	
Failure Rate: N/A	
Halogen Free: Yes	

General Information

Dimensions		
L	5.08mm MAX	
Н	6.6mm MAX	
Т	3.81mm MAX	
S	5.08mm +/-0.78mm	
LL	7mm MIN	
F	0.51mm +0.1/-0.025mm	

Specifications	
Capacitance:	750 pF
Capacitance Tolerance:	5%
Voltage DC:	1000 VDC
Dielectric Withstanding Voltage:	1,200 V
Temperature Range:	-55/+125C
Temperature Coefficient:	COG
Dissipation Factor:	0.10% 25C
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	100 GOhms

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

