KEMET Part Number: C2220C362JDGACTU

(C2220C362JDGAC7800)



SMD Comm C0G HV, Ceramic, 3600 pF, 5%, 1000 VDC, C0G, SMD, MLCC, Ultra-Stable, Low Loss, Class I, 2220



Supplier: KEMET Series: SMD Comm C0G HV Style: SMD Chip Description: SMD, MLCC, Ultra-Stable, Low Loss, Class I
Style: SMD Chip Secription: SMD, MLCC, Ultra-Stable, Low
Description: SMD, MLCC, Ultra-Stable, Low
Description:
2003, 01033 1
Features: Ultra-Stable, Low Loss, Class
RoHS: Yes
Termination: Tin
Marking: No
Chip Size: 2220

Conoral Information

Dimensions		
L	5.7mm +/-0.4mm	
W	5mm +/-0.4mm	
Т	1.6mm +/-0.20mm	
В	0.6mm +/-0.35mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	1000	

Specifications		
Capacitance:	3600 pF	
Capacitance Tolerance:	5%	
Voltage DC:	1000 VDC	
Dielectric Withstanding Voltage:	1,200 V	
Temperature Range:	-55/+125C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.10% 1kHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

