
KEMET Part Number: C0603C431J1GACTU

(C0603C431J1GAC7867)



SMD Comm COG, Ceramic, 430 pF, 5%, 100 VDC, COG, SMD, MLCC, Ultra-Stable, Low Loss, Class I, 0603



				Features:	Ultra-Stable, Low Loss, Class I
S			RoHS:	Yes	
			Termination:	Tin	
			Marking:	No	
				Chip Size:	0603
Dimensions					
	Din	Dimensions		Specifications	
	L	1.6mm +/-0.15mm		Capacitance:	430 pF

Dimensions				
L	1.6mm +/-0.15mm			
W	0.8mm +/-0.15mm			
Т	0.8mm +/-0.07mm			
S	0.7mm MIN			
В	0.35mm +/-0.15mm			

Packaging Specifications				
Packaging:	T&R, 180mm, Paper Tape			
Packaging Quantity:	4000			

Specifications		
Capacitance:	430 pF	
Capacitance Tolerance:	5%	
Voltage DC:	100 VDC	
Dielectric Withstanding Voltage:	250 V	
Temperature Range:	-55/+125C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.10% 1MHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

General Information

KEMET

SMD Chip

Loss, Class I

SMD Comm C0G

SMD, MLCC, Ultra-Stable, Low

Supplier:

Series:

Style:

Description:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

