KEMET Part Number: C0805C333J5JACTU

(C0805C333J5JAC7800)



SMD Comm U2J, Ceramic, 0.033 uF, 5%, 50 VDC, U2J, SMD, MLCC, Ultra-Stable, Low Loss, Class I, 0805



Dimensions		
L	2mm +/-0.2mm	
W	1.25mm +/-0.2mm	
Т	1.25mm +/-0.15mm	
S	0.75mm MIN	
В	0.5mm +/-0.25mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	2500	

General Information		
Supplier:	KEMET	
Series:	SMD Comm U2J	
Style:	SMD Chip	
Description:	SMD, MLCC, Ultra-Stable, Low Loss, Class I	
Features:	Ultra-Stable, Low Loss, Class I	
RoHS:	Yes	
Termination:	Tin	
Marking:	No	
Miscellaneous:	Note: Referee time for U2J dielectric for this part number is 1000 hours	
Chip Size:	0805	

Specifications		
Capacitance:	0.033 uF	
Capacitance Tolerance:	5%	
Voltage DC:	50 VDC	
Dielectric Withstanding Voltage:	125 V	
Temperature Range:	-55/+125C	
Temperature Coefficient:	U2J	
Dissipation Factor:	0.10% 1kHz 25C	
Aging Rate:	0.1% Loss/Decade Hour	
Insulation Resistance:	30.303 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

