
## KEMET Part Number: PHE448RB4470JR06

(F448BJ472J1K6C)



PHE448/F448, Film, Film/Foil Polypropylene, General Purpose, 4700 pF, 5%, 1600 VDC, 85C, Lead Spacing = 15mm



General Information	
Supplier:	KEMET
Series:	PHE448/F448
Dielectric:	Film/Foil Polypropylene
Style:	Radial
Features:	Pulse
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Miscellaneous:	Rthha= 82 C/W (85C), 0.2 m/s
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart)

Dimensions		
L	18mm MAX	
Н	12.5mm MAX	
Т	6.5mm MAX	
S	15mm +/-0.4mm	
LL	6mm -1mm	
F	0.8mm +/-0.05mm	
G	0.5mm NOM	

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1000

Specifications		
Capacitance:	4700 pF	
Capacitance Tolerance:	5%	
Voltage AC:	650 VAC	
Voltage DC:	1600 VDC, 1184 VDC (105C)	
Temperature Range:	-55/+105C	
Rated Temperature:	85C	
Dissipation Factor:	0.03% 1kHz, 0.05% 10kHz, 0.1% 100kHz	
Insulation Resistance:	6.383 GOhms	
Max dV/dt:	15000 V/us	
Inductance:	6 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

