
KEMET Part Number: SMC5.7223J100J33TR12

(F125PP223J100V, SMC100DJ5220JJ33T1)



SMC/F125, Film, Metallized PPS, General Purpose, 0.022 uF, 5%, 63 VAC, 100 VDC, 100C, 2220, 3mm



Note: '()' correspond to the letters used in the product bulletin

Dimensions		
Chip Size	2220	
L	5.7mm +/-0.2mm	
W	5mm +/-0.2mm	
Т	3mm +/-0.2mm	
F	0.5mm NOM	

Packaging Specifications	
Packaging:	T&R
Packaging Quantity:	2400

General Information		
Supplier:	KEMET	
Series:	SMC/F125	
Dielectric:	Metallized PPS	
Style:	SMD Chip	
Features:	High Stability	
RoHS:	Yes	

Specifications	
Capacitance:	0.022 uF
Capacitance Tolerance:	5%
Voltage AC:	63 VAC
Voltage DC:	100 VDC
Temperature Range:	-55/+125C
Rated Temperature:	100C
Dissipation Factor:	0.15% 1kHz, 0.25% 10kHz, 0.5% 100kHz
Insulation Resistance:	15 GOhms
Max dV/dt:	15 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

