## KEMET Part Number: PFR5471J400J11L4BULK

(F411JH471J400C)

L H T S


LL

F

G



PFR/F411, Film, Film/Foil Polypropylene, General Purpose, 470 pF, 5%, 400 VDC, 85C, Lead Spacing = 5mm



	G	
S		
Dir	nensions	
	7.2mm MAX	
	6mm MAX	
	4.5mm MAX	
	5mm -0.4mm	

4mm +1mm

0.5mm +/-0.05mm 0.5mm NOM

General Information		
Supplier:	KEMET	
Series:	PFR/F411	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Miscellaneous:	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult Kemet For Details.	

Specifications			
Capacitance:	470 pF		
Capacitance Tolerance:	5%		
Voltage AC:	220 VAC		
Voltage DC:	400 VDC		
Temperature Range:	-55/+100C		
Rated Temperature:	85C		
Dissipation Factor:	0.04% 1kHz, 0.04% 10kHz, 0.05% 100kHz		
Insulation Resistance:	63829.7872 GOhms		
Max dV/dt:	1000 V/us		
Inductance:	6 nH		

Packaging Specifications	
Bulk, Bag	
1000	
3	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

