

KEMET Part Number: PHE450RD5270JR06L2
(F450DD273J1K6Z)

PHE450/F450, Film, Double Metallized Polypropylene, General Purpose, 0.027 uF, 5%, 1600 VDC, 85C, Lead Spacing = 22.5mm



| General Information | |
|---------------------|---|
| Supplier: | KEMET |
| Series: | PHE450/F450 |
| Dielectric: | Double Metallized Polypropylene |
| Style: | Radial |
| Features: | Pulse |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Miscellaneous: | The Rated Voltage Decreases 1.3%/C Between +85C And +105C. Rthha= 58 C/W (85C), 0.2 m/s |

| Dimensions | |
|------------|-----------------|
| L | 26mm MAX |
| H | 14.5mm MAX |
| T | 6.5mm MAX |
| S | 22.5mm +/-0.4mm |
| LL | 18.5mm +0.5mm |
| F | 0.8mm +/-0.05mm |
| G | 0.5mm NOM |

| Specifications | |
|------------------------|---------------------------------------|
| Capacitance: | 0.027 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 650 VAC |
| Voltage DC: | 1600 VDC (85C), 1184 VDC (105C) |
| Temperature Range: | -55/+105C |
| Rated Temperature: | 85C |
| Dissipation Factor: | 0.03% 1kHz, 0.04% 10kHz, 0.15% 100kHz |
| Insulation Resistance: | 1111.111 GOhms |
| Max dV/dt: | 1800 V/us |
| Inductance: | 6 nH |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging: | Pizza, Box |
| Packaging Quantity: | 440 |