
KEMET Part Number: MDC10475K100A54P3TUBE

(F153AA475K100T, MDC100DA7470KA54P3L3)



MDC, Film, Metallized Polyester, Dual-In-Line, 4.7 uF, 10%, 63 VAC, 100 VDC, 85C, 10mm



General Information	
Supplier:	KEMET
Series:	MDC
Dielectric:	Metallized Polyester
Style:	Dual-In-Line
RoHS:	Yes
Lead:	L Leads

Dimensions	
L	13.5mm +/-0.2mm
W	12.2mm +/-0.2mm
Т	6.05mm +/-0.2mm
S	10mm +/-0.2mm
F	0.5mm +/-0.05mm

Specifications	
Capacitance:	4.7 uF
Capacitance Tolerance:	10%
Voltage AC:	63 VAC
Voltage DC:	100 VDC
Temperature Range:	-55/+125C
Rated Temperature:	85C
Dissipation Factor:	0.80% 1kHz, 1.50% 10kHz
Insulation Resistance:	1.0638 GOhms
Inductance:	4 nH

Packaging Specifications		
Packaging:	Bulk, Tube	
Packaging Quantity:	35	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

