

# Ultra Phosphor Oscilloscope



72-14520 UK  
72-14520 EU



72-14525 UK  
72-14525 EU



72-14530 UK  
72-14530 EU



72-14535 UK  
72-14535 EU

## Features

- Two and Four Channels with HD Colour 8" LCD Display
- Supports Plug-and-Play USB Storage Device to Communicate with PC
- Real-Time Continuous Hardware Waveform Recording and Waveform Analysis
- Multi-waveform Mathematical Operation Function
- Automatic Measurement of 34 Waveform Parameters
- Edge, Video and Pulse Width
- Waveform Capture Rate of Up to 50,000wfms/s
- Unique Waveform Recording and Replay Function
- Pass / Fail Detection



# Ultra Phosphor Oscilloscope



Parameter	72-14520 UK	72-14520 EU	72-14525 UK	72-14525 EU
Channel	2			
Bandwidth	70MHz		100MHz	
Sample Rate	1GS/s			
Rise Time	≤ 5ns		≤ 3.5ns	
Memory Depth	28Mpts (Each Channel)			
Waveform Acquisition Rate	50,000wfms/s			
Times Base Scale	5ns/div ~ 50s/div			
Input Coupling	(1MΩ ±2%)    (20pF ±3pF)			
Vertical Scale	1mV/div ~ 20V/div (1MΩ)			
DC Gain Accuracy	± 3%			
Waveform Record	65,000 Frames			
Trigger	Edge, Pulse Width, Slope, Video, Pattern. (Optional) Window, Runt, Time Out, Nth Edge, Delay, Duration, Setup/Hold RS232/UART, I2C			
Bus Decode	RS232/UART, I2C			
Waveform Operation	A+B, A-B, AxB, A/B, FFT, Logic Operation, Editable Advanced Filter			
Auto Measurement	Max, Min, High, Low, Middle, Pk-Pk, Ample, Mean, Cycle Mean, RMS, Cycle RMS, Area, Cycle Area, OverShoot, PreShoot, Period, Frequency, Rise, Fall, +Width, -Width, +Duty, -Duty, RiseDelay, FallDelay, Phase, FRR, FRF, FFR, FFF, LRF, LRR, LFR, LFF			
No. of Measurements	Display 5 measurements at the same time			
Measurement Statistic	Average, Max, Min, Standard Deviation, Number of Measurements			
Frequency Counter	Hardware 6 bits counter (channels are selectable)			
Standard Interface	USB-Host, USB Device, LAN, AUX Out (Trig Out, Pass/Fail)			
Plug Type	UK	EU	UK	EU

Parameter	72-14530 UK	72-14530 EU	72-14535 UK	72-14535 EU
Channel	4			
Bandwidth	70MHz		100MHz	
Sample Rate	1GS/s			
Rise Time	≤ 5ns		≤ 3.5ns	
Memory Depth	28Mpts (Each Channel)			
Waveform Acquisition Rate	50,000wfms/s			
Times Base Scale	5ns/div ~ 50s/div			
Input Coupling	(1MΩ ±2%)    (20pF ±3pF)			
Vertical Scale	1mV/div ~ 20V/div (1MΩ)			
DC Gain Accuracy	± 3%			
Waveform Record	65,000 Frames			
Trigger	Edge, Pulse Width, Slope, Video. (Optional) Window, Runt, Time Out, Nth Edge, Delay, Duration, Setup/Hold, Pattern, RS232/UART, I2C, SPI			



# Ultra Phosphor Oscilloscope



Parameter	72-14530 UK	72-14530 EU	72-14535 UK	72-14535 EU
Bus Decode	RS232/UART, I2C, SPI (Optional)			
Waveform Operation	A+B, A-B, AxB, A/B, FFT, Logic Operation, Editable Advanced Filter			
Auto Measurement	Max, Min, High, Low, Middle, Pk-Pk, Ample, Mean, Cycle Mean, RMS, Cycle RMS, Area, Cycle Area, OverShoot, PreShoot, Period, Frequency, Rise, Fall, +Width, -Width, +Duty, -Duty, RiseDelay, FallDelay, Phase, FRR, FRF, FFR, FFF, LRF, LRR, LFR, LFF			
No. of Measurements	Display 5 measurements at the same time			
Measurement Statistic	Average, Max, Min, Standard Deviation, Number of Measurements			
Frequency Counter	Hardware 6 bits counter (channels are selectable)			
Standard Interface	USB-Host, USB Device, LAN, AUX Out (Trig Out, Pass/Fail)			
Plug Type	UK	EU	UK	EU

## General Characteristics

Safety Rating	: CAT II 150V (1x), CAT II 300V (10x)
Power	: 100V ~ 240V AC, 50Hz/60Hz/400Hz
Display	: 8 Inches TFT Colour LCD Display with WVGA (800 × 480) Resolution
Colour	: White and Grey
Weight	: 3.5kg
Size	: 336mm × 164mm × 108mm

## Accessories

Digital Oscilloscope Unit, Mains Power Lead, Communications Software CD, USB Lead, Selectable 1:1/10:1 Passive Probes, User Manual.

## Part Number Table

Description	Part Number
Digital Ultra Phosphor Storage Oscilloscope, 2CH, 70MHz, 1GS/s, 28Mpts, UK	72-14520 UK
Digital Ultra Phosphor Storage Oscilloscope, 2CH, 70MHz, 1GS/s, 28Mpts, EU	72-14520 EU
Digital Ultra Phosphor Storage Oscilloscope, 2CH, 100MHz, 1GS/s, 28Mpts, UK	72-14525 UK
Digital Ultra Phosphor Storage Oscilloscope, 2CH, 100MHz, 1GS/s, 28Mpts, EU	72-14525 EU
Digital Ultra Phosphor Storage Oscilloscope, 4CH, 70MHz, 1GS/s, 28Mpts, UK	72-14530 UK
Digital Ultra Phosphor Storage Oscilloscope, 4CH, 70MHz, 1GS/s, 28Mpts, EU	72-14530 EU
Digital Ultra Phosphor Storage Oscilloscope, 4CH, 100MHz, 1GS/s, 28Mpts, UK	72-14535 UK
Digital Ultra Phosphor Storage Oscilloscope, 4CH, 100MHz, 1GS/s, 28Mpts, EU	72-14535 EU

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com  
 www.farnell.com  
 www.newark.com  
 www.cpc.co.uk

